

## CONDENSING UNITS HERMETIC UNITS

Hermetic compressor, crankcase heater where foreseen,  
 Basement in galvanized metal sheet and air condenser in copper tube  
 and aluminum fins with axial fan motors.  
 Liquid receiver with overpressure discharge device  
 Liquid and suction valves in standard models with thermal expansion valve.  
 In the water cooled version the compressor is equipped with cooling fan.  
 For R290 version the units are equipped with mini-channel condensers and approved components.

The units can be equipped with the following accessories:  
 Liquid line  
 Safety and control pressure switches  
 Liquid and oil separators  
 Electric box for power and condenser fan management  
 EC fans  
 Electronic remote monitoring or management



## TN -5°C/-15°C

### DATI TECNICI | TECHNICAL DATA | TECHNICAL DATA

C16.11/A

<b>Unità</b> <b>Unit</b> <b>Unit</b>	Tensione   Voltage   Voltage	volt/f/Hz	220/240-1-50HZ	
	Assorbimento   Absorption   Absorption	W	249	
		A	1.59	
	Compressore   Compressor   Kompressor	model	EMT45HDR	
		cc	4.4	
	Refrigerante   Coolant   Coolant	R134a		
Tipo Espansione Expansion management Expansion management	Capillare Exp. Capillary Kapillar Expansion			
<b>Condensazione</b> <b>Condensation</b> <b>Condensation</b>	Tipo cond.   Cond. type   Cond. type	aria		
<b>Dimensioni</b> <b>Sizes</b> <b>Sizes</b>	Diam. tubo liq.   Liq. line diam.   Liq. line diam.	mm	6	
	Diam. tubo asp.   Suct. line diam.   Suct. line diam.	mm	10	
	Larghezza   Width   Width	mm	300	
	Profondità   Depth   Depth	mm	420	
	Altezza   Height   Height	mm	275	
	Peso   Weight   Weight	kg	14	
<b>T</b>	Temp. Ambiente Max   Max ambient temp.   Max ambient temp.	°C	32	

### TABELLA DI SELEZIONE | SELECTION TABLE | AUSWAHLTABELLE

<b>TC -5°C</b>	W	253
<b>TC -10°C</b>	W	203
<b>TC -15°C</b>	W	159