

## CONDENSING UNITS

### HERMETIC UNITS

Hermetic compressor, crankcase heater where foreseen,  
 Basement in galvanized metal sheet and air condenser in copper tube  
 and aluminum fins with axial fan motors.  
 Liquid receiver with overpressure discharge device  
 Liquid and suction valves in standard models with thermal expansion valve.  
 In the water cooled version the compressor is equipped with cooling fan.  
 For R290 version the units are equipped with mini-channel condensers and approved components.

The units can be equipped with the following accessories:

- Liquid line
- Safety and control pressure switches
- Liquid and oil separators
- Electric box for power and condenser fan management
- EC fans
- Electronic remote monitoring or managment



## TN -5°C/-15°C

#### DATI TECNICI | TECHNICAL DATA | TECHNICAL DATA

V15.11/AT

Unità Unit Unit	Tensione   Voltage   Voltage	volt/f/Hz	220/240-1-50HZ
	Assorbimento   Absorption   Absorption	W	280
		A	1.8
	Compressore   Compressor   Kompressor	model	EMT6144Z
		cc	5.2
	Refrigerante   Coolant   Coolant		R134a
Condensazione Condensation Condensation	Tipo Espansione Expansion management Expansion management		Valvola Exp. Valve Expantionsventil
	Tipo cond.   Cond. type   Cond. type		aria
Dimensioni Sizes Sizes	Diam. tubo liq.   Liq. line diam.   Liq. line diam.	mm	6
	Diam. tubo asp.   Suct. line diam.   Suct. line diam.	mm	10
	Larghezza   Width   Width	mm	390
	Profondità   Depth   Depth	mm	540
	Altezza   Height   Height	mm	350
	Peso   Weight   Weight	kg	17
T	Temp. Ambiente Max   Max ambient temp.   Max ambient temp.	°C	43

#### TABELLA DI SELEZIONE | SELECTION TABLE | AUSWAHLTABELLE

	TC -5°C	W	367
	TC -10°C	W	308
	TC -15°C	W	257