V34.11/AT



CONDENSING UNITS

HERMETIC UNITS

Hermetic compressor, crankcase heater where foreseen,

Basement in galvanized metal sheet and air condenser in copper tube

and aluminum fins with axial fan motors.

Liquid receiver with overpressure discharge device

Liquid and suction valves in standard models with thermal expansion valve.

In the water cooled version the compressor is equipped with cooling fan.

For R290 version the units are equipped with mini-channel condensers and approved components.

The units can be equipped with the following accessories:

Liquid line

Safety and control pressure switches

Liquid and oil separators

Electric box for power and condenser fan management

EC fans

Electronic remote monitoring or managment





TN -5°C/-15°C

DATI TECNICI | TECHNICAL DATA | TECHNICAL DATA

	Tensione Voltage Voltage	volt/f/Hz	220/240-1-50HZ
Assorbimento Absorption Unit Unit Compressore Compressor Kompressor Unit Refrigerante Coolant Coolant Tipo Espansione Expansion management Expansion management	Assorbimento Absorption Absorption	W	1350
		A	7.2
		model	NJ6220Z
	Compressor Compressor Kompressor	сс	26.2
		R134a	
	Expansion management		Valvola Exp. Valve Expantionsventil
Condensazione Condensation Condensation	Tipo cond. Cond. type Cond. type		aria
Diam. tubo liq. Liq. line diam. Liq. line diam. Diam. tubo asp. Suct. line diam. Suct. line diam. Larghezza Width Width Sizes Sizes Profondità Depth Depth Altezza Height Height Peso Weight Weight	Diam. tubo liq. Liq. line diam. Liq. line diam.	mm	10
	Diam. tubo asp. Suct. line diam. Suct. line diam.	mm	12
	Larghezza Width Width	mm	390
	Profondità Depth Depth	mm	540
	Altezza Height Height	mm	350
	Peso Weight Weight	kg	35
	Temp. Ambiente Max Max ambient temp. Max ambient temp.	°C	43

TABELLA DI SELEZIONE | SELECTION TABLE | AUSWAHLTABELLE

	TC -5°C	W	1320
	TC -10°C	W	1048
	TC -15°C	W	806