V15.13/AT



CONDENSING UNITS

HERMETIC UNITS

Hermetic compressor, crankcase heater where foreseen,

Basement in galvanized metal sheet and air condenser in copper tube

and aluminum fins with axial fan motors.

Liquid receiver with overpressure discharge device

Liquid and suction valves in standard models with thermal expansion valve.

In the water cooled version the compressor is equipped with cooling fan.

For R290 version the units are equipped with mini-channel condensers and approved components.

The units can be equipped with the following accessories:

Liquid line

Safety and control pressure switches

Liquid and oil separators

Electric box for power and condenser fan management

Electronic remote monitoring or managment

DATI TECNICI | TECHNICAL DATA | TECHNICAL DATA



V15.13/AT

BT -25°C/-35°C

ATT TECHNOL TECHNICAL			V13.13/A1
Unità Unit Unit	Tensione Voltage Voltage	volt/f/Hz	220/240-1-50HZ
	Assorbimento Absorption Absorption	W	344
		A	1,97
	Compressor Compressor Kompressor	model	EMT2121GK
		cc	
	Refrigerante Coolant Coolant		R452A
	Tipo Espansione Expansion management Expansion management		Valvola Exp. Valve Expantionsventil
ondensazione ondensation ondensation	Tipo cond. Cond. type Cond. type		aria
Dimensioni Sizes Sizes	Diam. tubo liq. Liq. line diam. Liq. line diam.	mm	6
	Diam. tubo asp. Suct. line diam. Suct. line diam.	mm	10
	Larghezza Width Width	mm	300
	Profondità Depth Depth	mm	460
	Altezza Height Height	mm	275
	Peso Weight Weight	kg	20
	Temp. Ambiente Max Max ambient temp. Max ambient temp.	°C	43

TABELLA DI SELEZIONE | SELECTION TABLE | AUSWAHLTABELLE

TC -25°C	W	663
TC -30°C	W	484
TC -35°C	W	329