

CONDENSING UNITS

HERMETIC UNITS

Hermetic compressor, crankcase heater where foreseen,

Basement in galvanized metal sheet and air condenser in copper tube and aluminum fins with axial fan motors.

Liquid receiver with overpressure discharge device

Liquid and suction valves in standard models with thermal expansion valve.

In the water cooled version the compressor is equipped with cooling fan.

For R290 version the units are equipped with mini-channel condensers and approved components.

The units can be equipped with the following accessories:

Liquid line

Safety and control pressure switches

Liquid and oil separators

Electric box for power and condenser fan management

EC fans

Electronic remote monitoring or management



BT -25°C/-35°C

DATI TECNICI | TECHNICAL DATA | TECHNICAL DATA

V13.13

Unità Unit Unit	Tensione Voltage Voltage	volt/Hz	220/240-1-50HZ
	Assorbimento Absorption Absorption	W	586
		A	4,7
	Compressore Compressor Kompressor	model	AE2420ZFZ
		cc	9.35
	Refrigerante Coolant Coolant		R452A
Tipo Espansione Expansion management Expansion management		Valvola Exp. Valve Expantionsventil	
Condensazione Condensation Condensation	Tipo cond. Cond. type Cond. type		aria
Dimensioni Sizes Sizes	Diam. tubo liq. Liq. line diam. Liq. line diam.	mm	6
	Diam. tubo asp. Suct. line diam. Suct. line diam.	mm	10
	Larghezza Width Width	mm	300
	Profondità Depth Depth	mm	480
	Altezza Height Height	mm	275
	Peso Weight Weight	kg	20,8
T	Temp. Ambiente Max Max ambient temp. Max ambient temp.	°C	32

TABELLA DI SELEZIONE | SELECTION TABLE | AUSWAHLTABELLE

TC -25°C	W	433
TC -30°C	W	341
TC -35°C	W	260