

CONDENSING UNITS

HERMETIC UNITS

Hermetic compressor, crankcase heater where foreseen,

Basement in galvanized metal sheet and air condenser in copper tube and aluminum fins with axial fan motors.

Liquid receiver with overpressure discharge device

Liquid and suction valves in standard models with thermal expansion valve.

In the water cooled version the compressor is equipped with cooling fan.

For R290 version the units are equipped with mini-channel condensers and approved components.

The units can be equipped with the following accessories:

Liquid line

Safety and control pressure switches

Liquid and oil separators

Electric box for power and condenser fan management

EC fans

Electronic remote monitoring or management



TN -5°C/-15°C

DATI TECNICI | TECHNICAL DATA | TECHNICAL DATA

WC16.11/A

Unità Unit Unit	Tensione Voltage Voltage	volt/f/Hz	220/240-1-50HZ	
	Assorbimento Absorption Absorption	W	249	
		A	1.59	
	Compressore Compressor Kompressor	model	EMT45HDR	
		cc	4.4	
	Refrigerante Coolant Coolant	R134a		
Tipo Espansione Expansion management Expansion management	Valvola Exp. Valve Expantionsventil			
Condensazione Condensation Condensation	Tipo cond. Cond. type Cond. type	acqua		
Dimensioni Sizes Sizes	Diam. tubo liq. Liq. line diam. Liq. line diam.	mm	6	
	Diam. tubo asp. Suct. line diam. Suct. line diam.	mm	10	
	Larghezza Width Width	mm	300	
	Profondità Depth Depth	mm	480	
	Altezza Height Height	mm	250	
	Peso Weight Weight	kg	18,5	
T	Temp. Ambiente Max Max ambient temp. Max ambient temp.	°C		

TABELLA DI SELEZIONE | SELECTION TABLE | AUSWAHLTABELLE

TC -5°C	W	260
TC -10°C	W	208
TC -15°C	W	162