

CONDENSING UNITS HERMETIC UNITS

Hermetic compressor, crankcase heater where foreseen,
 Basement in galvanized metal sheet and air condenser in copper tube
 and aluminum fins with axial fan motors.
 Liquid receiver with overpressure discharge device
 Liquid and suction valves in standard models with thermal expansion valve.
 In the water cooled version the compressor is equipped with cooling fan.
 For R290 version the units are equipped with mini-channel condensers and approved components.

The units can be equipped with the following accessories:
 Liquid line
 Safety and control pressure switches
 Liquid and oil separators
 Electric box for power and condenser fan management
 EC fans
 Electronic remote monitoring or management



BT -25°C/-35°C

DATI TECNICI | TECHNICAL DATA | TECHNICAL DATA

WV150.13/A

Unità Unit Unit	Tensione Voltage Voltage	volt/Hz	220/240-1-50HZ
	Assorbimento Absorption Absorption	W	1665
		A	8,08
	Compressore Compressor Kompressor	model	NJ2212GK
		cc	34
	Refrigerante Coolant Coolant		R452A
Tipo Espansione Expansion management Expansion management		Valvola Exp. Valve Expansionsventil	
Condensazione Condensation Condensation	Tipo cond. Cond. type Cond. type		acqua
Dimensioni Sizes Sizes	Diam. tubo liq. Liq. line diam. Liq. line diam.	mm	10
	Diam. tubo asp. Suct. line diam. Suct. line diam.	mm	16
	Larghezza Width Width	mm	540
	Profondità Depth Depth	mm	450
	Altezza Height Height	mm	370
	Peso Weight Weight	kg	39
T	Temp. Ambiente Max Max ambient temp. Max ambient temp.	°C	

TABELLA DI SELEZIONE | SELECTION TABLE | AUSWAHLTABELLE

TC -25°C	W	1306
TC -30°C	W	1042
TC -35°C	W	809