

CONDENSING UNITS

HERMETIC UNITS

Hermetic compressor, crankcase heater where foreseen,
 Basement in galvanized metal sheet and air condenser in copper tube
 and aluminum fins with axial fan motors.
 Liquid receiver with overpressure discharge device
 Liquid and suction valves in standard models with thermal expansion valve.
 In the water cooled version the compressor is equipped with cooling fan.
 For R290 version the units are equipped with mini-channel condensers and approved components.

The units can be equipped with the following accessories:
 Liquid line
 Safety and control pressure switches
 Liquid and oil separators
 Electric box for power and condenser fan management
 EC fans
 Electronic remote monitoring or management



TN -5°C/-15°C

DATI TECNICI | TECHNICAL DATA | TECHNICAL DATA

WV200.3

Unità Unit Unit	Tensione Voltage Voltage	volt/f/Hz	220/240-1-50HZ	
	Assorbimento Absorption Absorption	W	2926	
		A	18,1	
	Compressore Compressor Kompressor	model	FH4524Z	
		cc	43,5	
	Refrigerante Coolant Coolant	R452A		
Tipo Espansione Expansion management Expansion management	Valvola Exp. Valve Expansionsventil			
Condensazione Condensation Condensation	Tipo cond. Cond. type Cond. type	acqua		
Dimensioni Sizes Sizes	Diam. tubo liq. Liq. line diam. Liq. line diam.	mm	10	
	Diam. tubo asp. Suct. line diam. Suct. line diam.	mm	16	
	Larghezza Width Width	mm	540	
	Profondità Depth Depth	mm	450	
	Altezza Height Height	mm	395	
	Peso Weight Weight	kg	40,5	
T	Temp. Ambiente Max Max ambient temp. Max ambient temp.	°C		

TABELLA DI SELEZIONE | SELECTION TABLE | AUSWAHLTABELLE

TC -5°C	W	3505
TC -10°C	W	2822
TC -15°C	W	2320