

V120.3/2VT

CONDENSING UNITS

HERMETIC UNITS

Hermetic compressor, crankcase heater where foreseen,
Basement in galvanized metal sheet and air condenser in copper tube
and aluminum fins with axial fan motors.
Liquid receiver with overpressure discharge device
Liquid and suction valves in standard models with thermal expansion valve.
In the water cooled version the compressor is equipped with cooling fan.
For R290 version the units are equipped with mini-channel condensers and approved components.

The units can be equipped with the following accessories:

Liquid line
Safety and control pressure switches
Liquid and oil separators
Electric box for power and condenser fan management
EC fans
Electronic remote monitoring or managment



TN -5°C/-15°C

DATI TECNICI | TECHNICAL DATA | TECHNICAL DATA

V120.3/2VT

Unità Unit Unit	Tensione Voltage Voltage	volt/f/Hz	220/240-1-50HZ
	Assorbimento Absorption Absorption	W	2212
		A	14,80
	Compressore Compressor Kompressor	model	CAJ4517Z
		cc	25,95
	Refrigerante Coolant Coolant		R452A
Condensazione Condensation Condensation	Tipo Espansione Expansion management Expansion management		Valvola Exp. Valve Expantionsventil
	Tipo cond. Cond. type Cond. type		aria
Dimensioni Sizes Sizes	Diam. tubo liq. Liq. line diam. Liq. line diam.	mm	10
	Diam. tubo asp. Suct. line diam. Suct. line diam.	mm	16
	Larghezza Width Width	mm	790
	Profondità Depth Depth	mm	580
	Altezza Height Height	mm	385
	Peso Weight Weight	kg	
T	Temp. Ambiente Max Max ambient temp. Max ambient temp.	°C	43

TABELLA DI SELEZIONE | SELECTION TABLE | AUSWAHLTABELLE

	TC -5°C	W	2445
	TC -10°C	W	2039
	TC -15°C	W	1665