

CONDENSING UNITS

HERMETIC UNITS

Hermetic compressor, crankcase heater where foreseen,
 Basement in galvanized metal sheet and air condenser in copper tube
 and aluminum fins with axial fan motors.
 Liquid receiver with overpressure discharge device
 Liquid and suction valves in standard models with thermal expansion valve.
 In the water cooled version the compressor is equipped with cooling fan.
 For R290 version the units are equipped with mini-channel condensers and approved components.

The units can be equipped with the following accessories:

- Liquid line
- Safety and control pressure switches
- Liquid and oil separators
- Electric box for power and condenser fan management
- EC fans
- Electronic remote monitoring or management



TN -5°C/-15°C

DATI TECNICI | TECHNICAL DATA | TECHNICAL DATA

V200.11/2V

Unità Unit Unit	Tensione Voltage Voltage	volt/f/Hz	220/240-1-50HZ	
	Assorbimento Absorption Absorption	W	3171	
		A	7,05	
	Compressore Compressor Kompressor	model	FH4525Y	
		cc	74,25	
	Refrigerante Coolant Coolant	R134a		
Tipo Espansione Expansion management Expansion management	Valvola Exp. Valve Expansionsventil			
Condensazione Condensation Condensation	Tipo cond. Cond. type Cond. type	aria		
Dimensioni Sizes Sizes	Diam. tubo liq. Liq. line diam. Liq. line diam.	mm	10	
	Diam. tubo asp. Suct. line diam. Suct. line diam.	mm	16	
	Larghezza Width Width	mm	790	
	Profondità Depth Depth	mm	580	
	Altezza Height Height	mm	385	
	Peso Weight Weight	kg	56	
T	Temp. Ambiente Max Max ambient temp. Max ambient temp.	°C	32	

TABELLA DI SELEZIONE | SELECTION TABLE | AUSWAHLTABELLE

TC -5°C	W	3844
TC -10°C	W	3063
TC -15°C	W	2390