

## LOW NOISE CONDENSING UNITS SCROLL

scroll compressor  
 casing lined with soundproofing material  
 Mini-channel condenser  
 muffler on the delivery of semi-hermetic compressors  
 High pressure switch with fixed calibration and low pressure adjustable calibration with automatic rearm.  
 Liquid receiver with overpressure discharge device, liquid line valve, liquid / moisture indicator dehydrator filter and liquid solenoid valve  
 Electrical panel for starter power and condenser fan management

optionals:  
 compressor management by inverter  
 Partial or total heat recovery.  
 Oil and liquid separator  
 Hot gas defrost direct or with reverse cycle  
 Electronic remote monitoring or management  
 EC fans



# BT -25°C/-35°C

### DATI TECNICI | TECHNICAL DATA | TECHNICAL DATA

AMU3BSCC0475T3N

<b>Unità</b> <b>Unit</b> <b>Unit</b>	Tensione   Voltage   Voltage	volt/Hz	400/3+N/50HZ
	Assorbimento   Absorption   Absorption	W	6306
	Compressore   Compressor   Kompressor	A	14,08
		model	ZF18
	Refrigerante   Coolant   Coolant	cc	130
<b>Condensazione</b> <b>Condensation</b> <b>Condensation</b>	Tipo cond.   Cond. type   Cond. type		R452A
	Tipo cond.   Cond. type   Cond. type		aria
<b>Dimensioni</b> <b>Sizes</b> <b>Sizes</b>	Diam. tubo liq.   Liq. line diam.   Liq. line diam.	mm	12
	Diam. tubo asp.   Suct. line diam.   Suct. line diam.	mm	28
	Larghezza   Width   Width	mm	1270
	Profondità   Depth   Depth	mm	660
	Altezza   Height   Height	mm	1135
	Peso   Weight   Weight	kg	172

### TABELLA DI SELEZIONE | SELECTION TABLE | AUSWAHLTABELLE

	<b>TC -25°C</b>	W	7487
	<b>TC -30°C</b>	W	6040
	<b>TC -35°C</b>	W	4762