

LOW NOISE CONDENSING UNITS SCROLL

scroll compressor
 casing lined with soundproofing material
 Mini-channel condenser
 muffler on the delivery of semi-hermetic compressors
 High pressure switch with fixed calibration and low pressure adjustable calibration with automatic rearm.
 Liquid receiver with overpressure discharge device, liquid line valve, liquid / moisture indicator dehydrator filter and liquid solenoid valve
 Electrical panel for starter power and condenser fan management

optionals:
 compressor management by inverter
 Partial or total heat recovery.
 Oil and liquid separator
 Hot gas defrost direct or with reverse cycle
 Electronic remote monitoring or management
 EC fans



BT -25°C/-35°C

DATI TECNICI | TECHNICAL DATA | TECHNICAL DATA

AMU3BSCC0475T3N

Unità Unit Unit	Tensione Voltage Voltage	volt/Hz	400/3+N/50HZ
	Assorbimento Absorption Absorption	W	6306
	Compressore Compressor Kompressor	A	14,08
		model	ZF18
	Refrigerante Coolant Coolant	cc	130
Condensazione Condensation Condensation			R452A
	Tipo cond. Cond. type Cond. type	aria	
Dimensioni Sizes Sizes	Diam. tubo liq. Liq. line diam. Liq. line diam.	mm	12
	Diam. tubo asp. Suct. line diam. Suct. line diam.	mm	28
	Larghezza Width Width	mm	1270
	Profondità Depth Depth	mm	660
	Altezza Height Height	mm	1135
	Peso Weight Weight	kg	172

TABELLA DI SELEZIONE | SELECTION TABLE | AUSWAHLTABELLE

	TC -25°C	W	7487
	TC -30°C	W	6040
	TC -35°C	W	4762