

## CONDENSING UNITS

### SEMIHERMETIC

#### Semihermetic Compressor

Basement in galvanized metal sheet and air condenser in copper tube

and aluminum fins with axial fan motors

Liquid receiver with overpressure discharge device

Liquid and suction line valves.

Anti-vibration mounts

In the water cooled version the compressor is equipped with cooling fan.



The units can be equipped with the following accessories:

Liquid line

Safety and control pressure switches

Liquid and oil separators

Partial or total heat recovery.

Hot gas defrost direct or with reverse cycle

Electric box for power and condenser fan management

EC fans

Electronic remote monitoring or management



## BT -25°C/-35°C

#### DATI TECNICI | TECHNICAL DATA | TECHNICAL DATA

UABSED023T03N4

<b>Unità</b> <b>Unit</b> <b>Unit</b>	Tensione   Voltage   Voltage	volt/f/Hz	400/3+N/50HZ
	Assorbimento   Absorption   Absorption	W	6200
		A	10,5
	Compressore   Compressor   Kompressor	model	H403CS
		cc	22,83
	Refrigerante   Coolant   Coolant		R452A
Tipo Espansione Expansion management Expansion management		Valvola Exp. Valve Expansionsventil	
<b>Condensazione</b> <b>Condensation</b> <b>Condensation</b>	Tipo cond.   Cond. type   Cond. type		aria
<b>Dimensioni</b> <b>Sizes</b> <b>Sizes</b>	Diam. tubo liq.   Liq. line diam.   Liq. line diam.	mm	16
	Diam. tubo asp.   Suct. line diam.   Suct. line diam.	mm	28
	Larghezza   Width   Width	mm	984
	Profondità   Depth   Depth	mm	750
	Altezza   Height   Height	mm	596
	Peso   Weight   Weight	kg	127
<b>T</b>	Temp. Ambiente Max   Max ambient temp.   Max ambient temp.	°C	32

#### TABELLA DI SELEZIONE | SELECTION TABLE | AUSWAHLTABELLE

<b>TC -25°C</b>	W	6045
<b>TC -30°C</b>	W	4841
<b>TC -35°C</b>	W	3775