

CONDENSING UNITS

SEMIHERMETIC

Semihermetic Compressor
 Basement in galvanized metal sheet and air condenser in copper tube and aluminum fins with axial fan motors
 Liquid receiver with overpressure discharge device
 Liquid and suction line valves.
 Anti-vibration mounts
 In the water cooled version the compressor is equipped with cooling fan.

The units can be equipped with the following accessories:

- Liquid line
- Safety and control pressure switches
- Liquid and oil separators
- Partial or total heat recovery.
- Hot gas defrost direct or with reverse cycle
- Electric box for power and condenser fan management
- EC fans
- Electronic remote monitoring or management



BT -25°C/-35°C

DATI TECNICI | TECHNICAL DATA | TECHNICAL DATA

UABSED085T03N6

| | | | |
|--|--|---|--------------|
| Unità Unit Unit | Tensione Voltage Voltage | volt/f/Hz | 400/3+N/50HZ |
| | Assorbimento Absorption Absorption | W | 26600 |
| | | A | 45 |
| | Compressore Compressor Kompressor | model | H2500CS |
| | | cc | 85,01 |
| | Refrigerante Coolant Coolant | | R452A |
| Tipo Espansione Expansion management Expansion management | | Valvola Exp. Valve Expansionsventil | |
| Condensazione Condensation Condensation | Tipo cond. Cond. type Cond. type | | aria |
| Dimensioni Sizes Sizes | Diam. tubo liq. Liq. line diam. Liq. line diam. | mm | 28 |
| | Diam. tubo asp. Suct. line diam. Suct. line diam. | mm | 54 |
| | Larghezza Width Width | mm | 2550 |
| | Profondità Depth Depth | mm | 1340 |
| | Altezza Height Height | mm | 1200 |
| | Peso Weight Weight | kg | 420 |
| T | Temp. Ambiente Max Max ambient temp. Max ambient temp. | °C | 32 |

TABELLA DI SELEZIONE | SELECTION TABLE | AUSWAHLTABELLE

| | | |
|-----------------|---|-------|
| TC -25°C | W | 22870 |
| TC -30°C | W | 18005 |
| TC -35°C | W | 13701 |