

CONDENSING UNITS

SEMIHERMETIC

Semihermetic Compressor
 Basement in galvanized metal sheet and air condenser in copper tube and aluminum fins with axial fan motors
 Liquid receiver with overpressure discharge device
 Liquid and suction line valves.
 Anti-vibration mounts
 In the water cooled version the compressor is equipped with cooling fan.

The units can be equipped with the following accessories:

- Liquid line
- Safety and control pressure switches
- Liquid and oil separators
- Partial or total heat recovery.
- Hot gas defrost direct or with reverse cycle
- Electric box for power and condenser fan management
- EC fans
- Electronic remote monitoring or management



TN -5°C/-15°C

DATI TECNICI | TECHNICAL DATA | TECHNICAL DATA

UATSED004T03N6

Unità Unit Unit	Tensione Voltage Voltage	volt/f/Hz	400/3+N/50HZ
	Assorbimento Absorption Absorption	W	1300
		A	2,4
	Compressore Compressor Kompressor	model	H80CC
		cc	4,42
	Refrigerante Coolant Coolant		R452A
Tipo Espansione Expansion management Expansion management		Valvola Exp. Valve Expansionsventil	
Condensazione Condensation Condensation	Tipo cond. Cond. type Cond. type		aria
Dimensioni Sizes Sizes	Diam. tubo liq. Liq. line diam. Liq. line diam.	mm	10
	Diam. tubo asp. Suct. line diam. Suct. line diam.	mm	16
	Larghezza Width Width	mm	829
	Profondità Depth Depth	mm	650
	Altezza Height Height	mm	460
	Peso Weight Weight	kg	72
T	Temp. Ambiente Max Max ambient temp. Max ambient temp.	°C	32

TABELLA DI SELEZIONE | SELECTION TABLE | AUSWAHLTABELLE

TC -5°C	W	2533
TC -10°C	W	2149
TC -15°C	W	1801