

## CONDENSING UNITS

### SEMIHERMETIC

Semihermetic Compressor  
 Basement in galvanized metal sheet and air condenser in copper tube and aluminum fins with axial fan motors  
 Liquid receiver with overpressure discharge device  
 Liquid and suction line valves.  
 Anti-vibration mounts  
 In the water cooled version the compressor is equipped with cooling fan.

The units can be equipped with the following accessories:

- Liquid line
- Safety and control pressure switches
- Liquid and oil separators
- Partial or total heat recovery.
- Hot gas defrost direct or with reverse cycle
- Electric box for power and condenser fan management
- EC fans
- Electronic remote monitoring or management



## TN -5°C/-15°C

#### DATI TECNICI | TECHNICAL DATA | TECHNICAL DATA

UATSED009T03N4

<b>Unità</b> <b>Unit</b> <b>Unit</b>	Tensione   Voltage   Voltage	volt/f/Hz	400/3+N/50HZ
	Assorbimento   Absorption   Absorption	W	3600
		A	6
	Compressore   Compressor   Kompressor	model	H201CC
		cc	9,16
	Refrigerante   Coolant   Coolant		R452A
Tipo Espansione Expansion management Expansion management		Valvola Exp. Valve Expansionsventil	
<b>Condensazione</b> <b>Condensation</b> <b>Condensation</b>	Tipo cond.   Cond. type   Cond. type		aria
<b>Dimensioni</b> <b>Sizes</b> <b>Sizes</b>	Diam. tubo liq.   Liq. line diam.   Liq. line diam.	mm	10
	Diam. tubo asp.   Suct. line diam.   Suct. line diam.	mm	18
	Larghezza   Width   Width	mm	984
	Profondità   Depth   Depth	mm	750
	Altezza   Height   Height	mm	501
	Peso   Weight   Weight	kg	86
<b>T</b>	Temp. Ambiente Max   Max ambient temp.   Max ambient temp.	°C	32

#### TABELLA DI SELEZIONE | SELECTION TABLE | AUSWAHLTABELLE

<b>TC -5°C</b>	W	5457
<b>TC -10°C</b>	W	4635
<b>TC -15°C</b>	W	3894