

CONDENSING UNITS

SEMIHERMETIC

Semihermetic Compressor

Basement in galvanized metal sheet and air condenser in copper tube

and aluminum fins with axial fan motors

Liquid receiver with overpressure discharge device

Liquid and suction line valves.

Anti-vibration mounts

In the water cooled version the compressor is equipped with cooling fan.



The units can be equipped with the following accessories:

Liquid line

Safety and control pressure switches

Liquid and oil separators

Partial or total heat recovery.

Hot gas defrost direct or with reverse cycle

Electric box for power and condenser fan management

EC fans

Electronic remote monitoring or management



TN -5°C/-15°C

DATI TECNICI | TECHNICAL DATA | TECHNICAL DATA

UATSED010T03N6

Unità Unit Unit	Tensione Voltage Voltage	volt/f/Hz	400/3+N/50HZ
	Assorbimento Absorption Absorption	W	3600
		A	6
	Compressore Compressor Kompressor	model	H221CC
		cc	9,88
	Refrigerante Coolant Coolant		R452A
Tipo Espansione Expansion management Expansion management		Valvola Exp. Valve Expansionsventil	
Condensazione Condensation Condensation	Tipo cond. Cond. type Cond. type		aria
Dimensioni Sizes Sizes	Diam. tubo liq. Liq. line diam. Liq. line diam.	mm	12
	Diam. tubo asp. Suct. line diam. Suct. line diam.	mm	22
	Larghezza Width Width	mm	984
	Profondità Depth Depth	mm	750
	Altezza Height Height	mm	596
	Peso Weight Weight	kg	90
T	Temp. Ambiente Max Max ambient temp. Max ambient temp.	°C	32

TABELLA DI SELEZIONE | SELECTION TABLE | AUSWAHLTABELLE

TC -5°C	W	5894
TC -10°C	W	4990
TC -15°C	W	4170