

LOW NOISE CONDENSING UNITS

HERMETIC

Hermetic compressor
 casing lined with soundproofing material
 Mini-channel condenser
 muffler on the delivery of semi-hermetic compressors
 High pressure switch with fixed calibration and low pressure adjustable calibration with automatic rearm.
 Liquid receiver with overpressure discharge device, liquid line valve, liquid / moisture indicator dehydrator filter and liquid solenoid valve
 Electrical panel for starter power and condenser fan management

optionals:
 compressor management by inverter
 Partial or total heat recovery.
 Oil and liquid separator
 Hot gas defrost direct or with reverse cycle
 Electronic remote monitoring or management
 EC fans



TN -5°C/-15°C

DATI TECNICI | TECHNICAL DATA | TECHNICAL DATA

AMU2TALU0334T11N

Unità Unit Unit	Tensione Voltage Voltage	volt/Hz	400/3+N/50HZ
	Assorbimento Absorption Absorption	W	3700
	Compressore Compressor Kompressor	A	6,4
		model	TAG4534Y
	Refrigerante Coolant Coolant	cc	100,7
Condensazione Condensation Condensation	Tipo cond. Cond. type Cond. type		R134a
			aria
Dimensioni Sizes Sizes	Diam. tubo liq. Liq. line diam. Liq. line diam.	mm	12
	Diam. tubo asp. Suct. line diam. Suct. line diam.	mm	22
	Larghezza Width Width	mm	1270
	Profondità Depth Depth	mm	660
	Altezza Height Height	mm	610
	Peso Weight Weight	kg	86

TABELLA DI SELEZIONE | SELECTION TABLE | AUSWAHLTABELLE

	TC -5°C	W	4910
	TC -10°C	W	3706
	TC -15°C	W	2657