

LOW NOISE CONDENSING UNITS SEMI-HERMETIC

Semi-hermetic compressor
 casing lined with soundproofing material
 Mini-channel condenser
 muffler on the delivery of semi-hermetic compressors
 High pressure switch with fixed calibration and low pressure adjustable calibration with automatic rearm.
 Liquid receiver with overpressure discharge device, liquid line valve, liquid / moisture indicator
 dehydrator filter and liquid solenoid valve
 Electrical panel for starter power and condenser fan management

optionals:
 compressor management by inverter
 Partial or total heat recovery.
 Oil and liquid separator
 Hot gas defrost direct or with reverse cycle
 Electronic remote monitoring or management
 EC fans



BT -25°C/-35°C

DATI TECNICI | TECHNICAL DATA | TECHNICAL DATA

AMU4BSEB0660T9N

Unità Unit Unit	Tensione Voltage Voltage	volt/Hz	400/3+N/50HZ
	Assorbimento Absorption Absorption	W	11250
	Compressore Compressor Kompressor	A	21,7
		model	4PES-12Y
	Refrigerante Coolant Coolant	cc	48,5
Condensazione Condensation Condensation	Tipo cond. Cond. type Cond. type		aria
	Diam. tubo liq. Liq. line diam. Liq. line diam.	mm	16
Dimensioni Sizes Sizes	Diam. tubo asp. Suct. line diam. Suct. line diam.	mm	35
	Larghezza Width Width	mm	1480
	Profondità Depth Depth	mm	810
	Altezza Height Height	mm	1665
	Peso Weight Weight	kg	335

TABELLA DI SELEZIONE | SELECTION TABLE | AUSWAHLTABELLE

	TC -25°C	W	10610
	TC -30°C	W	8334
	TC -35°C	W	6337