

CONDENSING UNITS

SEMIHERMETIC

Semihermetic Compressor

Basement in galvanized metal sheet and air condenser in copper tube

and aluminum fins with axial fan motors

Liquid receiver with overpressure discharge device

Liquid and suction line valves.

Anti-vibration mounts

In the water cooled version the compressor is equipped with cooling fan.



The units can be equipped with the following accessories:

Liquid line

Safety and control pressure switches

Liquid and oil separators

Partial or total heat recovery.

Hot gas defrost direct or with reverse cycle

Electric box for power and condenser fan management

EC fans

Electronic remote monitoring or management



TN -5°C/-15°C

DATI TECNICI | TECHNICAL DATA | TECHNICAL DATA

UATSEB007T03N6

| | | | |
|--|--|---|--------------|
| Unità Unit Unit | Tensione Voltage Voltage | volt/f/Hz | 400/3+N/50HZ |
| | Assorbimento Absorption Absorption | W | 2190 |
| | | A | 4,5 |
| | Compressore Compressor Kompressor | model | 2HES-2Y |
| | | cc | 6,51 |
| | Refrigerante Coolant Coolant | | R452A |
| Tipo Espansione Expansion management Expansion management | | Valvola Exp. Valve Expansionsventil | |
| Condensazione Condensation Condensation | Tipo cond. Cond. type Cond. type | | aria |
| Dimensioni Sizes Sizes | Diam. tubo liq. Liq. line diam. Liq. line diam. | mm | 10 |
| | Diam. tubo asp. Suct. line diam. Suct. line diam. | mm | 16 |
| | Larghezza Width Width | mm | 984 |
| | Profondità Depth Depth | mm | 750 |
| | Altezza Height Height | mm | 501 |
| | Peso Weight Weight | kg | 91 |
| T | Temp. Ambiente Max Max ambient temp. Max ambient temp. | °C | 32 |

TABELLA DI SELEZIONE | SELECTION TABLE | AUSWAHLTABELLE

| | | |
|-----------------|---|------|
| TC -5°C | W | 3801 |
| TC -10°C | W | 3202 |
| TC -15°C | W | 2665 |