C22SQ3RB0495B3



COMPRESSORS RACKS

ENERFROST

Ener Frost® is the multicompressor racks series equipped with 2, 3 or 4 compressors, two of which are regulated by two vector inverters independently

Some features, minimum liquid level monitoring with alarm, compressors support floating frame, high pressure switch on each compressor, low pressure switch and intervenction of inverter of the compressors in the event of an electronic failure

Electrical panel complete with magneto-thermal and differentials for compressor, compressor headers fan and crankcase heater, double safety transformer for auxiliaries, programmable controller

Enerfrost Units can be equipped with the following accessories:

Partial or total heat recovery.

Hot gas defrost direct or with reverse cycle

FC fans

Electronic remote monitoring or managment or WRC remote control





BT -25°C/-35°C

DATI TECNICI TECHNICAL DATA TECHNICAL DATA			C22SQ3RB0495B3	
Unità Unit Unit	Tensione Voltage Voltage	volt/f/Hz	400/3+N/50HZ	
	Assorbimento Absorption Absorption	W	9362	
		A	18	
	Compressor Compressor Kompressor	model	2CES-3Y	
		сс	16,2	
	Comp. con inverter. Inverter Comp. Inverter Comp.	n°	2	
	Refrigerante Coolant Coolant		R452A	
Condensazione Condensation Condensation	Tipo cond. Cond. type Cond. type		remoto	
Dimensioni Sizes Sizes	Diam. tubo liq. Liq. line diam. Liq. line diam.	mm	35	
	Diam. tubo asp. Suct. line diam. Suct. line diam.	mm	16	
	Diam. uscita cond. Cond. inlet diam. Cond. inlet diam.	mm	18	
	Diam. ritorno cond. Cond. return diam. Cond. return diam.	mm	16	
	Larghezza Width Width	mm	1550	
	Profondità Depth Depth	mm	790	
	Altezza Height Height	mm	1240	
	Peso Weight Weight	kg	485	
TABELLA DI SELEZIONE SELECTION TABLE AUSWAHLTABELLE			MIN	MAX
	TC -25°C	W	1987	9536
	TC -30°C	W	1594	7651
	TC -35°C	W	1275	6120