## C22SQ3RT1730B3



## **COMPRESSORS RACKS**

## **ENERFROST**

Ener Frost® is the multicompressor racks series equipped with 2, 3 or 4 compressors, two of which are regulated by two vector inverters independently

Some features, minimum liquid level monitoring with alarm, compressors support floating frame, high pressure switch on each compressor, low pressure switch and intervenction of inverter of the compressors in the event of an electronic failure

Electrical panel complete with magneto-thermal and differentials for compressor, compressor headers fan and crankcase heater, double safety transformer for auxiliaries, programmable controller

Enerfrost Units can be equipped with the following accessories:

Partial or total heat recovery.

Hot gas defrost direct or with reverse cycle

EC fans

Electronic remote monitoring or managment or WRC remote control





## TN -5°C/-15°C

DATI TECNICI   TECHNICAL DATA   TECHNICAL DATA			C22SQ3RT1730B3		
Unità Unit Unit	Tensione   Voltage   Voltage	volt/f/Hz	400/3+N/50HZ		
	Assorbimento   Absorption   Absorption	W	10746		
		A	20		
	Compressor   Compressor   Kompressor	model	2CES-4Y		
		cc	16,2		
	Comp. con inverter.   Inverter Comp.   Inverter Comp.	n°	2		
	Refrigerante   Coolant   Coolant		R452A		
Condensazione Condensation Condensation	Tipo cond.   Cond. type   Cond. type		remoto		
Dimensioni Sizes Sizes	Diam. tubo liq.   Liq. line diam.   Liq. line diam.	mm	35		
	Diam. tubo asp.   Suct. line diam.   Suct. line diam.	mm	18		
	Diam. uscita cond.   Cond. inlet diam.   Cond. inlet diam.	mm	22		
	Diam. ritorno cond.   Cond. return diam.   Cond. return diam.	mm	18		
	Larghezza   Width   Width	mm	1550		
	Profondità   Depth   Depth	mm	790		
	Altezza   Height   Height	mm	1240		
	Peso   Weight   Weight	kg	485		
TABELLA DI SELEZIONE   SELECTION TABLE   AUSWAHLTABELLE			MIN	MAX	
	TC -5°C	W	4959	23803	
	TC -10°C	W	4220	20253	
	TC -15°C	W	3568	17123	