## C23SQ3RT18890B3



## COMPRESSORS RACKS ENERFROST

Ener Frost $\circledast$  is the multicompressor racks series equipped with 2, 3 or 4 compressors, two of which are regulated by two vector inverters independently

Some features, minimum liquid level monitoring with alarm, compressors support floating frame,

high pressure switch on each compressor, low pressure switch and intervenction of inverter of the compressors in the event of an electronic failure

Electrical panel complete with magneto-thermal and differentials for compressor, compressor headers fan and crankcase heater, double safety transformer for auxiliaries, programmable controller

Enerfrost Units can be equipped with the following accessories:

Partial or total heat recovery.

Hot gas defrost direct or with reverse cycle

EC fans

Electronic remote monitoring or managment or WRC remote control



C23SQ3RT18890B3

## **IN -5°C/-15°C**

## DATI TECNICI | TECHNICAL DATA | TECHNICAL DATA

			0200001	110000000
Unità Unit Unit	Tensione   Voltage   Voltage	volt/f/Hz	400/3+N/50HZ	
	Assorbimento   Absorption   Absorption	W	111000	
		А	186	
	Compressore   Compressor   Kompressor	model	6HE-35Y	
		сс	110.5	
	Comp. con inverter.   Inverter Comp.   Inverter Comp.	n°	2	
	Refrigerante   Coolant   Coolant		R452A	
Condensazione Condensation Condensation	Tipo cond.   Cond. type   Cond. type		remoto	
Dimensioni Sizes Sizes	Diam. tubo liq.   Liq. line diam.   Liq. line diam.	mm	28	
	Diam. tubo asp.   Suct. line diam.   Suct. line diam.	mm	28	
	Diam. uscita cond.   Cond. inlet diam.   Cond. inlet diam.	mm	28	
	Diam. ritorno cond.   Cond. return diam.   Cond. return diam.	mm	28	
	Larghezza   Width   Width	mm	900	
	Profondità   Depth   Depth	mm	660	
	Altezza   Height   Height	mm	800	
	Peso   Weight   Weight	kg	2105	
ABELLA DI SELEZIONE   SELECTION TABLE   AUSWAHLTABELLE			MIN	MAX
	TC -5°C	W	34084	231773
TC -10°C		W	27930	189923
	TC -15°C	W	22634	153912

Sicaf - Compressors racks - Enerfrost - C23SQ3RT18890B3 - 2 Agosto 2025