C22SQ3VT0380B3



C22SQ3VT0380B3

COMPRESSORS RACKS ENERFROST

Ener Frost® is the multicompressor racks series equipped with 2, 3 or 4 compressors, two of which are regulated by two vector inverters independently

Some features, minimum liquid level monitoring with alarm, compressors support floating frame, high pressure switch on each compressor, low pressure switch and intervenction of inverter of the compressors in the event of an electronic failure

Electrical panel complete with magneto-thermal and differentials for compressor, compressor headers fan and crankcase heater, double safety transformer for auxiliaries, programmable controller

Enerfrost Units can be equipped with the following accessories:

Partial or total heat recovery.

Hot gas defrost direct or with reverse cycle

EC fans

Electronic remote monitoring or managment or WRC remote control



I TN -5°C/-15°C

DATI TECNICI | TECHNICAL DATA | TECHNICAL DATA

			0220001	10000000
Unità Unit Unit	Tensione Voltage Voltage	volt/f/Hz	400/3+N/50HZ	
	Assorbimento Absorption Absorption	W	2530	
		А	4	
	Compressore Compressor Kompressor	model	2KES-05Y	
		сс	4,06	
	Comp. con inverter. Inverter Comp. Inverter Comp.	n°	2	
	Refrigerante Coolant Coolant		R452A	
Condensazione Condensation Condensation	Tipo cond. Cond. type Cond. type		aria	
Dimensioni Sizes Sizes	Diam. tubo liq. Liq. line diam. Liq. line diam.	mm	18	
	Diam. tubo asp. Suct. line diam. Suct. line diam.	mm	12	
	Diam. uscita cond. Cond. inlet diam. Cond. inlet diam.	mm	2X350	
	Diam. ritorno cond. Cond. return diam. Cond. return diam.	mm	3800	
	Larghezza Width Width	mm	1575	
	Profondità Depth Depth	mm	805	
	Altezza Height Height	mm	1865	
	Peso Weight Weight	kg	490	
TABELLA DI SELEZIONE SELECTION TABLE AUSWAHLTABELLE			MIN	MAX
	TC -5°C	W	1259	6043
	TC -10°C	W	1039	4983
	TC -15°C	W	841	4036

Sicaf - Compressors racks - Enerfrost - C22SQ3VT0380B3 - 2 Agosto 2025