

COMPRESSORS RACKS
ENERFROST

Ener Frost® is the multicompressor racks series equipped with 2, 3 or 4 compressors, two of which are regulated by two vector inverters independently

Some features, minimum liquid level monitoring with alarm, compressors support floating frame, high pressure switch on each compressor; low pressure switch and intervention of inverter of the compressors in the event of an electronic failure

Electrical panel complete with magneto-thermal and differentials for compressor, compressor headers fan and crankcase heater, double safety transformer for auxiliaries, programmable controller

Enerfrost Units can be equipped with the following accessories:

Partial or total heat recovery.

Hot gas defrost direct or with reverse cycle

EC fans

Electronic remote monitoring or managment or WRC remote control



TN -5°C/-15°C

DATI TECNICI | TECHNICAL DATA | TECHNICAL DATA

C22SQ3VT0530B3

Unità Unit Unit	Tensione Voltage Voltage	volt/f/Hz	400/3+N/50HZ
	Assorbimento Absorption Absorption	W	3514
		A	6
	Compressore Compressor Kompressor	model	2JES-07Y
		cc	5,21
	Comp. con inverter. Inverter Comp. Inverter Comp.	n°	2
Condensazione Condensation Condensation	Refrigerante Coolant Coolant		R452A
	Tipo cond. Cond. type Cond. type		aria
Dimensioni Sizes Sizes	Diam. tubo liq. Liq. line diam. Liq. line diam.	mm	22
	Diam. tubo asp. Suct. line diam. Suct. line diam.	mm	12
	Diam. uscita cond. Cond. inlet diam. Cond. inlet diam.	mm	2X350
	Diam. ritorno cond. Cond. return diam. Cond. return diam.	mm	3800
	Larghezza Width Width	mm	1575
	Profondità Depth Depth	mm	805
	Altezza Height Height	mm	1865
	Peso Weight Weight	kg	490

TABELLA DI SELEZIONE | SELECTION TABLE | AUSWAHLTABELLE

MINMAX

TC -5°C	W	1643	7883
TC -10°C	W	1368	6563
TC -15°C	W	1121	5379