C22SQ3VT4500B3



C22SQ3VT4500B3

COMPRESSORS RACKS ENERFROST

Ener Frost® is the multicompressor racks series equipped with 2, 3 or 4 compressors, two of which are regulated by two vector inverters independently

Some features, minimum liquid level monitoring with alarm, compressors support floating frame, high pressure switch on each compressor, low pressure switch and intervenction of inverter of the compressors in the event of an electronic failure

Electrical panel complete with magneto-thermal and differentials for compressor, compressor headers fan and crankcase heater, double safety transformer for auxiliaries, programmable controller

Enerfrost Units can be equipped with the following accessories:

Partial or total heat recovery.

Hot gas defrost direct or with reverse cycle

EC fans

Electronic remote monitoring or managment or WRC remote control



I TN -5°C/-15°C

DATI TECNICI | TECHNICAL DATA | TECHNICAL DATA

				1150025
Unità Unit Unit	Tensione Voltage Voltage	volt/f/Hz	400/3+N/50HZ	
	Assorbimento Absorption Absorption	W	26818	
		А	50	
	Compressore Compressor Kompressor	model	4TES-12Y	
		сс	41,3	
	Comp. con inverter. Inverter Comp. Inverter Comp.	n°	2	
	Refrigerante Coolant Coolant		R452A	
Condensazione Condensation Condensation	Tipo cond. Cond. type Cond. type		aria	
Dimensioni Sizes Sizes	Diam. tubo liq. Liq. line diam. Liq. line diam.	mm	54	
	Diam. tubo asp. Suct. line diam. Suct. line diam.	mm	28	
	Diam. uscita cond. Cond. inlet diam. Cond. inlet diam.	mm	2X630	
	Diam. ritorno cond. Cond. return diam. Cond. return diam.	mm	18950	
	Larghezza Width Width	mm	3535	
	Profondità Depth Depth	mm	1150	
	Altezza Height Height	mm	2285	
	Peso Weight Weight	kg	1363	
ABELLA DI SELEZIO	DNE SELECTION TABLE AUSWAHLTABELLE		MIN	MAX
	TC -5°C	W	12806	61465
TC -10°C		W	10761	51649
	TC -15°C	W	8956	42987

Sicaf - Compressors racks - Enerfrost - C22SQ3VT4500B3 - 3 Agosto 2025