

COMPRESSORS RACKS

COMPRESSORS RACKS ON/OFF

Compressors racks with 2, 3 or 4 compressors, on/off or in alternative with single inverter driven compressor,

Electrical panel complete with magneto-thermal and differentials for compressor, compressor headers fan and crankcase heater, double safety transformer for auxiliaries, programmed controller

The compressors rack can be equipped with the following accessories:

- Partial or total heat recovery.
- Hot gas direct defrost or with reverse cycle
- EC fans
- Electronic remote monitoring or management



BT -25°C/-35°C

DATI TECNICI | TECHNICAL DATA | TECHNICAL DATA

CSS3R5BALA0190M3N

Unità Unit Unit	Tensione Voltage Voltage	volt/f/Hz	220/240-1-50HZ
	Assorbimento Absorption Absorption	W	3135
		A	12
	Compressore Compressor Kompressor	model	
		cc	26
Comp. con inverter. Inverter Comp. Inverter Comp.	n°		
	Refrigerante Coolant Coolant		R452A
Condensazione Condensation Condensation	Tipo cond. Cond. type Cond. type		remoto
Dimensioni Sizes Sizes	Diam. tubo liq. Liq. line diam. Liq. line diam.	mm	10
	Diam. tubo asp. Suct. line diam. Suct. line diam.	mm	10
	Diam. uscita cond. Cond. inlet diam. Cond. inlet diam.	mm	10
	Diam. ritorno cond. Cond. return diam. Cond. return diam.	mm	10
	Larghezza Width Width	mm	900
	Profondità Depth Depth	mm	660
	Altezza Height Height	mm	800
	Peso Weight Weight	kg	

TABELLA DI SELEZIONE | SELECTION TABLE | AUSWAHLTABELLE

MIN

MAX

TC -25°C

W

429

2574

TC -30°C

W

339

2030

TC -35°C

W

265

1589