

COMPRESSORS RACKS

COMPRESSORS RACKS ON/OFF

Compressors racks with 2, 3 or 4 compressors, on/off or in alternative with single inverter driven compressor,

Electrical panel complete with magneto-thermal and differentials for compressor, compressor headers fan and crankcase heater, double safety transformer for auxiliaries, programmed controller

The compressors rack can be equipped with the following accessories:

- Partial or total heat recovery.
- Hot gas direct defrost or with reverse cycle
- EC fans
- Electronic remote monitoring or management



TN -5°C/-15°C

DATI TECNICI | TECHNICAL DATA | TECHNICAL DATA

CSS4R5TALA0825M3N

Unità Unit Unit	Tensione Voltage Voltage	volt/Hz	220/240-1-50HZ
	Assorbimento Absorption Absorption	W	5300
		A	21.6
	Compressore Compressor Kompressor	model	
		cc	26
Comp. con inverter. Inverter Comp. Inverter Comp.	n°		
Condensazione Condensation Condensation	Refrigerante Coolant Coolant		R452A
	Tipo cond. Cond. type Cond. type		remoto
Dimensioni Sizes Sizes	Diam. tubo liq. Liq. line diam. Liq. line diam.	mm	16
	Diam. tubo asp. Suct. line diam. Suct. line diam.	mm	16
	Diam. uscita cond. Cond. inlet diam. Cond. inlet diam.	mm	16
	Diam. ritorno cond. Cond. return diam. Cond. return diam.	mm	16
	Larghezza Width Width	mm	900
	Profondità Depth Depth	mm	660
	Altezza Height Height	mm	800
	Peso Weight Weight	kg	

TABELLA DI SELEZIONE | SELECTION TABLE | AUSWAHLTABELLE

		MIN	MAX
	TC -5°C	W	1186 9486
	TC -10°C	W	998 7978
	TC -15°C	W	828 6620