C23SQ3RB9430B3

COMPRESSORS RACKS

ENERFROST

Ener Frost® is the multicompressor racks series equipped with 2, 3 or 4 compressors, two of which are regulated by two vector inverters independently
Some features, minimum liquid level monitoring with alarm, compressors support floating frame, high pressure switch on each compressor, low pressure switch and intervention of inverter of the compressors in the event of an electronic failure
Electrical panel complete with magneto-thermal and differentials for compressor, compressor headers fan and crankcase heater, double safety transformer for auxiliaries, programmable controller

Enerfrost Units can be equipped with the following accessories:
Partial or total heat recovery.
Hot gas defrost direct or with reverse cycle
EC fans
Electronic remote monitoring or managment or WRC remote control

BT -25°C/-35°C

DATI TECNICI | TECHNICAL DATA | TECHNICAL DATA			C23SQ3RB9430B3
Unità Unit Unit	Tensione | Voltage | Voltage	volt/f/Hz	400/3+N/50HZ
	Assorbimento | Absorption | Absorption	W	111000
		A	186
	Compressore | Compressor | Kompressor	model	6GE-34Y
		cc	126.8
	Comp. con inverter. | Inverter Comp. | Inverter Comp.	n°	2
	Refrigerante | Coolant | Coolant		R452A
Condensazione Condensation Condensation	Tipo cond. | Cond. type | Cond. type		remoto
Dimensioni Sizes Sizes	Diam. tubo liq. | Liq. line diam. | Liq. line diam.	mm	28
	Diam. tubo asp. | Suct. line diam. | Suct. line diam.	mm	28
	Diam. uscita cond. | Cond. inlet diam. | Cond. inlet diam.	mm	28
	Diam. ritorno cond. | Cond. return diam. | Cond. return diam.	mm	28
	Larghezza | Width | Width	mm	900
	Profondità | Depth | Depth	mm	660
	Altezza | Height | Height	mm	800
	Peso | Weight | Weight	kg	2084

TABELLA DI SELEZIONE | SELECTION TABLE | AUSWAHLTABELLE		MIN	MAX
TC -25°C	W	17702	**120376**
TC -30°C	W	13943	**94813**
TC -35°C	W	10728	**72949**