

COMPRESSORS RACKS

ENERFROST

Ener Frost® is the multicompressor racks series equipped with 2, 3 or 4 compressors, two of which are regulated by two vector inverters independently

Some features, minimum liquid level monitoring with alarm, compressors support floating frame, high pressure switch on each compressor; low pressure switch and intervention of inverter of the compressors in the event of an electronic failure

Electrical panel complete with magneto-thermal and differentials for compressor, compressor headers fan and crankcase heater, double safety transformer for auxiliaries, programmable controller

Enerfrost Units can be equipped with the following accessories:

Partial or total heat recovery.

Hot gas defrost direct or with reverse cycle

EC fans

Electronic remote monitoring or management or WRC remote control



BT -25°C/-35°C

DATI TECNICI | TECHNICAL DATA | TECHNICAL DATA

CSS3A5BALA0250M3N

Unità Unit Unit	Tensione Voltage Voltage	volt/Hz	220/240-1-50HZ
	Assorbimento Absorption Absorption	W	3990
		A	15
	Compressore Compressor Kompressor	model	
		cc	34
Comp. con inverter. Inverter Comp. Inverter Comp.	n°		
	Refrigerante Coolant Coolant		R452A
Condensazione Condensation Condensation	Tipo cond. Cond. type Cond. type		aria
Dimensioni Sizes Sizes	Diam. tubo liq. Liq. line diam. Liq. line diam.	mm	12
	Diam. tubo asp. Suct. line diam. Suct. line diam.	mm	12
	Diam. uscita cond. Cond. inlet diam. Cond. inlet diam.	mm	2X350
	Diam. ritorno cond. Cond. return diam. Cond. return diam.	mm	3800
	Larghezza Width Width	mm	1575
	Profondità Depth Depth	mm	805
	Altezza Height Height	mm	1865
	Peso Weight Weight	kg	

TABELLA DI SELEZIONE | SELECTION TABLE | AUSWAHLTABELLE

MIN

MAX

TC -25°C

W

737

4417

TC -30°C

W

579

3472

TC -35°C

W

443

2657