

## COMPRESSORS RACKS

### COMPRESSORS RACKS ON/OFF

Compressors racks with 2, 3 or 4 compressors, on/off or in alternative with single inverter driven compressor,

Electrical panel complete with magneto-thermal and differentials for compressor, compressor headers fan and crankcase heater, double safety transformer for auxiliaries, programmed controller

The compressors rack can be equipped with the following accessories:

Partial or total heat recovery.

Hot gas direct defrost or with reverse cycle

EC fans

Electronic remote monitoring or management



## TN -5°C/-15°C

#### DATI TECNICI | TECHNICAL DATA | TECHNICAL DATA

CSS4V5TALA1050M3N

<b>Unità</b> <b>Unit</b> <b>Unit</b>	Tensione   Voltage   Voltage	volt/Hz	220/240-1-50HZ
	Assorbimento   Absorption   Absorption	W	6620
		A	26
	Compressore   Compressor   Kompressor	model	
		cc	34
Comp. con inverter.   Inverter Comp.   Inverter Comp.	n°		
	Refrigerante   Coolant   Coolant		R452A
<b>Condensazione</b> <b>Condensation</b> <b>Condensation</b>	Tipo cond.   Cond. type   Cond. type		aria
<b>Dimensioni</b> <b>Sizes</b> <b>Sizes</b>	Diam. tubo liq.   Liq. line diam.   Liq. line diam.	mm	16
	Diam. tubo asp.   Suct. line diam.   Suct. line diam.	mm	16
	Diam. uscita cond.   Cond. inlet diam.   Cond. inlet diam.	mm	2X350
	Diam. ritorno cond.   Cond. return diam.   Cond. return diam.	mm	3800
	Larghezza   Width   Width	mm	1575
	Profondità   Depth   Depth	mm	805
	Altezza   Height   Height	mm	1865
	Peso   Weight   Weight	kg	

#### TABELLA DI SELEZIONE | SELECTION TABLE | AUSWAHLTABELLE

		MIN	MAX
	<b>TC -5°C</b>	W	1577
	<b>TC -10°C</b>	W	1321
	<b>TC -15°C</b>	W	1086