## C22SQ3AT2170B11



C22SQ3AT2170B11

## COMPRESSORS RACKS ENERFROST

Ener Frost® is the multicompressor racks series equipped with 2, 3 or 4 compressors, two of which are regulated by two vector inverters independently

Some features, minimum liquid level monitoring with alarm, compressors support floating frame, high pressure switch on each compressor, low pressure switch and intervenction of inverter of the compressors in the event of an electronic failure

Electrical panel complete with magneto-thermal and differentials for compressor, compressor headers fan and crankcase heater, double safety transformer for auxiliaries, programmable controller

Enerfrost Units can be equipped with the following accessories:

Partial or total heat recovery.

Hot gas defrost direct or with reverse cycle

EC fans

Electronic remote monitoring or managment or WRC remote control



## **I** TN -5°C/-15°C

## DATI TECNICI | TECHNICAL DATA | TECHNICAL DATA

Unità Unit Unit	Tensione   Voltage   Voltage	volt/f/Hz	400/3+N/50HZ	
	Assorbimento   Absorption   Absorption	W	21612	
		А	38	
	Compressore   Compressor   Kompressor	model	4VES-10Y	
		СС	34,7	
	Comp. con inverter.   Inverter Comp.   Inverter Comp.	n°	2	
	Refrigerante   Coolant   Coolant		R134a	
Condensazione Condensation Condensation	Tipo cond.   Cond. type   Cond. type		aria	
Dimensioni Sizes Sizes	Diam. tubo liq.   Liq. line diam.   Liq. line diam.	mm	54	
	Diam. tubo asp.   Suct. line diam.   Suct. line diam.	mm	22	
	Diam. uscita cond.   Cond. inlet diam.   Cond. inlet diam.	mm	3X500	
	Diam. ritorno cond.   Cond. return diam.   Cond. return diam.	mm	14700	
	Larghezza   Width   Width	mm	2220	
	Profondità   Depth   Depth	mm	805	
	Altezza   Height   Height	mm	1850	
	Peso   Weight   Weight	kg	1017	
TABELLA DI SELEZIONE   SELECTION TABLE   AUSWAHLTABELLE			MIN	MAX
	TC -5°C	W	6257	30033
	TC -10°C	W	5239	25147
	TC -15°C	W	4337	20814

Sicaf - Compressors racks - Enerfrost - C22SQ3AT2170B11 - 2 Agosto 2025