CS22NQ3RB0200E2



CS22NQ3RB0200E2

COMPRESSORS RACKS ENERFROST

Ener Frost® is the multicompressor racks series equipped with 2, 3 or 4 compressors, two of which are regulated by two vector inverters independently

Some features, minimum liquid level monitoring with alarm, compressors support floating frame, high pressure switch on each compressor, low pressure switch and intervenction of inverter of the compressors in the event of an electronic failure

Electrical panel complete with magneto-thermal and differentials for compressor, compressor headers fan and crankcase heater, double safety transformer for auxiliaries, programmable controller

Enerfrost Units can be equipped with the following accessories:

Partial or total heat recovery.

Hot gas defrost direct or with reverse cycle

EC fans

Electronic remote monitoring or managment or WRC remote control



BT -25°C/-35°C

DATI TECNICI | TECHNICAL DATA | TECHNICAL DATA

	Tensione Voltage Voltage	volt/f/Hz	400/3+	N/50HZ
Unità Unit Unit	Assorbimento Absorption Absorption	W	4300	
		А	15	
	Compressore Compressor Kompressor	model	NJ2212GS	
		сс	64	
	Comp. con inverter. Inverter Comp. Inverter Comp.	n°	2	
	Refrigerante Coolant Coolant		R452A	
Condensazione Condensation Condensation	Tipo cond. Cond. type Cond. type		remoto	
Dimensioni Sizes Sizes	Diam. tubo liq. Liq. line diam. Liq. line diam.	mm	12	
	Diam. tubo asp. Suct. line diam. Suct. line diam.	mm	18	
	Diam. uscita cond. Cond. inlet diam. Cond. inlet diam.	mm	10	
	Diam. ritorno cond. Cond. return diam. Cond. return diam.	mm	10	
	Larghezza Width Width	mm	950	
	Profondità Depth Depth	mm	600	
	Altezza Height Height	mm	800	
	Peso Weight Weight	kg		
TABELLA DI SELEZIONE SELECTION TABLE AUSWAHLTABELLE			MIN	MAX
	TC -25°C	W	582	2790
TC -30°C		W	466	2235
	TC -35°C	W	370	1772

Sicaf - Compressors racks - Enerfrost - CS22NQ3RB0200E2 - 2 Agosto 2025