

## COMPRESSORS RACKS

### ENERFROST

Ener Frost® is the multicompressor racks series equipped with 2, 3 or 4 compressors, two of which are regulated by two vector inverters independently

Some features, minimum liquid level monitoring with alarm, compressors support floating frame, high pressure switch on each compressor; low pressure switch and intervention of inverter of the compressors in the event of an electronic failure

Electrical panel complete with magneto-thermal and differentials for compressor, compressor headers fan and crankcase heater, double safety transformer for auxiliaries, programmable controller

Enerfrost Units can be equipped with the following accessories:

Partial or total heat recovery.

Hot gas defrost direct or with reverse cycle

EC fans

Electronic remote monitoring or management or WRC remote control



## TN -5°C/-15°C

#### DATI TECNICI | TECHNICAL DATA | TECHNICAL DATA

CS22NQ3ST0460E2

|  |   |           |              |  |
|--|---|-----------|--------------|--|
| <b>Unità</b><br><b>Unit</b><br><b>Unit</b>                         | Tensione   Voltage   Voltage                                  | volt/f/Hz | 400/3+N/50HZ |  |
|  | Assorbimento   Absorption   Absorption                        | W         | 3600         |  |
|  |   | A         | 11.5         |  |
|  | Compressore   Compressor   Kompressor                         | model     | NJ9232GS     |  |
|  |   | cc        | 52           |  |
|  | Comp. con inverter.   Inverter Comp.   Inverter Comp.         | n°        | 2            |  |
| Refrigerante   Coolant   Coolant                                   | R452A   |           |              |  |
| <b>Condensazione</b><br><b>Condensation</b><br><b>Condensation</b> | Tipo cond.   Cond. type   Cond. type                          | remoto    |              |  |
| <b>Dimensioni</b><br><b>Sizes</b><br><b>Sizes</b>                  | Diam. tubo liq.   Liq. line diam.   Liq. line diam.           | mm        | 12           |  |
|  | Diam. tubo asp.   Suct. line diam.   Suct. line diam.         | mm        | 12           |  |
|  | Diam. uscita cond.   Cond. inlet diam.   Cond. inlet diam.    | mm        | 12           |  |
|  | Diam. ritorno cond.   Cond. return diam.   Cond. return diam. | mm        | 12           |  |
|  | Larghezza   Width   Width                                     | mm        | 950          |  |
|  | Profondità   Depth   Depth                                    | mm        | 600          |  |
|  | Altezza   Height   Height                                     | mm        | 800          |  |
|  | Peso   Weight   Weight  | kg        |              |  |

#### TABELLA DI SELEZIONE | SELECTION TABLE | AUSWAHLTABELLE

MIN

MAX

**TC -5°C**

W

1105

**5301**

**TC -10°C**

W

925

**4436**

**TC -15°C**

W

762

**3658**