CS22NQ3ST0270E11



COMPRESSORS RACKS

ENERFROST

 $Ener\ Frost @is\ the\ multicompressor\ racks\ series\ equipped\ with\ 2,\ 3\ or\ 4\ compressors,\ two\ of\ which$ are regulated by two vector inverters independently

Some features, minimum liquid level monitoring with alarm, compressors support floating frame, high pressure switch on each compressor, low pressure switch and intervenction of inverter of the compressors in the event of an electronic failure

Electrical panel complete with magneto-thermal and differentials for compressor, compressor headers fan and crankcase heater, double safety transformer for auxiliaries, programmable controller

Enerfrost Units can be equipped with the following accessories:

Partial or total heat recovery.

Hot gas defrost direct or with reverse cycle

EC fans

Electronic remote monitoring or managment or WRC remote control



1 TN -5°C/-15°C

DATI TECNICI TECHNICAL DATA TECHNICAL DATA		CS22NQ3ST0270E11		
Unità Unit Unit	Tensione Voltage Voltage	volt/f/Hz	400/3+N/50HZ	
	Assorbimento Absorption Absorption	W	3600	
		A	11.5	
	Compressor Compressor Kompressor	model	NJ6220ZX	
		СС	52	
	Comp. con inverter. Inverter Comp. Inverter Comp.	n°	2	
	Refrigerante Coolant Coolant		R134a	
Condensazione Condensation Condensation	Tipo cond. Cond. type Cond. type		remoto	
Dimensioni Sizes Sizes	Diam. tubo liq. Liq. line diam. Liq. line diam.	mm	12	
	Diam. tubo asp. Suct. line diam. Suct. line diam.	mm	12	
	Diam. uscita cond. Cond. inlet diam. Cond. inlet diam.	mm	12	
	Diam. ritorno cond. Cond. return diam. Cond. return diam.	mm	12	
	Larghezza Width Width	mm	950	
	Profondità Depth Depth	mm	600	
	Altezza Height Height	mm	800	
	Peso Weight Weight	kg		
TABELLA DI SELEZIONE SELECTION TABLE AUSWAHLTABELLE			MIN	MAX
	TC -5°C	W	726	3482
TC -10°C		W	577	2766
	TC -15°C	W	442	2122