

COMPRESSORS RACKS

ENERFROST

Ener Frost® is the multicompressor racks series equipped with 2, 3 or 4 compressors, two of which are regulated by two vector inverters independently

Some features, minimum liquid level monitoring with alarm, compressors support floating frame, high pressure switch on each compressor; low pressure switch and intervention of inverter of the compressors in the event of an electronic failure

Electrical panel complete with magneto-thermal and differentials for compressor, compressor headers fan and crankcase heater, double safety transformer for auxiliaries, programmable controller

Enerfrost Units can be equipped with the following accessories:

Partial or total heat recovery.

Hot gas defrost direct or with reverse cycle

EC fans

Electronic remote monitoring or management or WRC remote control



TN -5°C/-15°C

DATI TECNICI | TECHNICAL DATA | TECHNICAL DATA

CS23NQ3ST0550E11

Unità Unit Unit	Tensione Voltage Voltage	volt/f/Hz	400/3+N/50HZ	
	Assorbimento Absorption Absorption	W	3600	
		A	11.5	
	Compressore Compressor Kompressor	model	NJ6226ZX	
		cc	102	
	Comp. con inverter. Inverter Comp. Inverter Comp.	n°	2	
Refrigerante Coolant Coolant	R134a			
Condensazione Condensation Condensation	Tipo cond. Cond. type Cond. type	remoto		
Dimensioni Sizes Sizes	Diam. tubo liq. Liq. line diam. Liq. line diam.	mm	12	
	Diam. tubo asp. Suct. line diam. Suct. line diam.	mm	12	
	Diam. uscita cond. Cond. inlet diam. Cond. inlet diam.	mm	12	
	Diam. ritorno cond. Cond. return diam. Cond. return diam.	mm	12	
	Larghezza Width Width	mm	1550	
	Profondità Depth Depth	mm	790	
	Altezza Height Height	mm	1240	
	Peso Weight Weight	kg		

TABELLA DI SELEZIONE | SELECTION TABLE | AUSWAHLTABELLE

MIN

MAX

TC -5°C

W

1030

7000

TC -10°C

W

849

5771

TC -15°C

W

687

4667