CS23NQ3VT0550E11



CS23NQ3VT0550E11

COMPRESSORS RACKS ENERFROST

Ener Frost \circledast is the multicompressor racks series equipped with 2, 3 or 4 compressors, two of which are regulated by two vector inverters independently

Some features, minimum liquid level monitoring with alarm, compressors support floating frame, high pressure switch on each compressor, low pressure switch and intervenction of inverter of the compressors in the event of an electronic failure

Electrical panel complete with magneto-thermal and differentials for compressor, compressor headers fan and crankcase heater, double safety transformer for auxiliaries, programmable controller

Enerfrost Units can be equipped with the following accessories:

Partial or total heat recovery.

Hot gas defrost direct or with reverse cycle

EC fans

Electronic remote monitoring or managment or WRC remote control



I TN -5°C/-15°C

DATI TECNICI | TECHNICAL DATA | TECHNICAL DATA

Unità Unit Unit	Tensione Voltage Voltage	volt/f/Hz	400/3+N/50HZ	
	Assorbimento Absorption Absorption	W	3600	
		А	11.5	
	Compressore Compressor Kompressor	model	NJ6226ZX	
		сс	102	
	Comp. con inverter. Inverter Comp. Inverter Comp.	n°	2	
	Refrigerante Coolant Coolant		R134a	
Condensazione Condensation Condensation	Tipo cond. Cond. type Cond. type		aria	
Dimensioni Sizes Sizes	Diam. tubo liq. Liq. line diam. Liq. line diam.	mm	12	
	Diam. tubo asp. Suct. line diam. Suct. line diam.	mm	12	
	Diam. uscita cond. Cond. inlet diam. Cond. inlet diam.	mm	2X350	
	Diam. ritorno cond. Cond. return diam. Cond. return diam.	mm	3800	
	Larghezza Width Width	mm	1575	
	Profondità Depth Depth	mm	805	
	Altezza Height Height	mm	1865	
	Peso Weight Weight	kg		
TABELLA DI SELEZIONE SELECTION TABLE AUSWAHLTABELLE			MIN	MAX
	TC -5°C	W	1127	7659
	TC -10°C	W	919	6249
	TC -15°C	W	736	5000

Sicaf - Compressors racks - Enerfrost - CS23NQ3VT0550E11 - 3 Agosto 2025