

COMPRESSORS RACKS

ENERFROST

Ener Frost® is the multicompressor racks series equipped with 2, 3 or 4 compressors, two of which are regulated by two vector inverters independently

Some features, minimum liquid level monitoring with alarm, compressors support floating frame, high pressure switch on each compressor; low pressure switch and intervention of inverter of the compressors in the event of an electronic failure

Electrical panel complete with magneto-thermal and differentials for compressor, compressor headers fan and crankcase heater, double safety transformer for auxiliaries, programmable controller

Enerfrost Units can be equipped with the following accessories:

Partial or total heat recovery.

Hot gas defrost direct or with reverse cycle

EC fans

Electronic remote monitoring or management or WRC remote control



BT -25°C/-35°C

DATI TECNICI | TECHNICAL DATA | TECHNICAL DATA

CS23NQ3VB0290E2

| | | | | |
|--|---|---------|--------------|--|
| Unità Unit Unit | Tensione Voltage Voltage | volt/Hz | 400/3+N/50HZ | |
| | Assorbimento Absorption Absorption | W | 2200 | |
| | | A | 9 | |
| | Compressore Compressor Kompressor | model | NJ2212GS | |
| | | cc | 96 | |
| | Comp. con inverter. Inverter Comp. Inverter Comp. | n° | 2 | |
| Refrigerante Coolant Coolant | R452A | | | |
| Condensazione Condensation Condensation | Tipo cond. Cond. type Cond. type | aria | | |
| Dimensioni Sizes Sizes | Diam. tubo liq. Liq. line diam. Liq. line diam. | mm | 12 | |
| | Diam. tubo asp. Suct. line diam. Suct. line diam. | mm | 12 | |
| | Diam. uscita cond. Cond. inlet diam. Cond. inlet diam. | mm | 2X350 | |
| | Diam. ritorno cond. Cond. return diam. Cond. return diam. | mm | 3800 | |
| | Larghezza Width Width | mm | 1575 | |
| | Profondità Depth Depth | mm | 805 | |
| | Altezza Height Height | mm | 1865 | |
| | Peso Weight Weight | kg | | |

TABELLA DI SELEZIONE | SELECTION TABLE | AUSWAHLTABELLE

MIN

MAX

TC -25°C

W

741

5035

TC -30°C

W

583

3963

TC -35°C

W

446

3030