

MONOBLOCKS AND REFRIGERATED SYSTEMS STRADDLE MOUNTING

Straddle mounting as standard, optional panel through the wall installation

- Electronic control instrument
- Expansion device: capillary tube
- Cable for door heater (on all low temperature units)
- Cable for cold room lighting
- Fixed calibration low pressure switch
- High pressure switch on all three-phase units and on single-phase models
- ACM122-152 (this outfit complies with the provisions of the "pressure equipment directive 97/23/CE)
- Condensate evaporation tray with safety overflow drain
- Drain heater
- Hermetic compressor
- Hot gas defrost
- Filter on the liquid line
- Prearrangement for door micro switch connection



TN +5°C/-5°C

DATI TECNICI | TECHNICAL DATA | TECHNICAL DATA

ACM058

Unità Unit Unit	Tensione Voltage Voltage	volt/f/Hz	230/1/50
	Assorbimento Absorption Absorption	W	920
	Compressore Compressor Kompressor	m ³ /h	2,49
	Tipo comp. Comp. Type Comp. Type	E/S	E
	Sbrinamento Defrost Defrost	El / Gc	Gc
	Refrigerante Coolant Coolant		R452A
Condensatore Condensator Condensator	Ventole Fans Fans	n°x Ø	1X254
	Portata aria Air flow Air flow	m ³ /h	1050
Evaporatore Evaporator Evaporator	Ventole Fans Fans	n°x Ø	1X200
	Portata aria Air flow Air flow	m ³ /h	550
	Gittata Air-throw Air-throw	m	m.5
Dimensioni Sizes Sizes	Larghezza Width Width	mm	900
	Profondità Depth Depth	mm	530
	Altezza Height Height	mm	920
	Peso Weight Weight	kg	56

TABELLA DI SELEZIONE | SELECTION TABLE | AUSWAHLTABELLE

m³

W

TA +20°C	TC +5°C	16,8	1514
	TC 0°C	13,3	1290
	TC -5°C	9,6	1088
TA +32°C	TC +5°C	12,7	1216
	TC 0°C	9,2	1023
	TC -5°C	7,1	851
TA +43°C	TC +5°C	8,2	1006
	TC 0°C	5,8	838
	TC -5°C	4,7	696