

MONOBLOCKS AND REFRIGERATED SYSTEMS STRADDLE MOUNTING

Straddle mounting as standard, optional panel through the wall installation

Electronic control instrument
Expansion device: capillary tube
Cable for door heater (on all low temperature units)
Cable for cold room lighting
Fixed calibration low pressure switch
High pressure switch on all three-phase units and on single-phase models
ACM122-152 (this outfit complies with the provisions of the "pressure equipment directive 97/23/CE)
Condensate evaporation tray with safety overflow drain
Drain heater
Hermetic compressor
Hot gas defrost
Filter on the liquid line
Prearrangement for door micro switch connection



TN +5°C/-5°C

DATI TECNICI | TECHNICAL DATA | TECHNICAL DATA

ACM100

Unità Unit Unit	Tensione Voltage Voltage	volt/f/Hz	230/1/50
	Assorbimento Absorption Absorption	W	1470
	Compressore Compressor Kompressor	m ³ /h	3,89
	Tipo comp. Comp. Type Comp. Type	E/S	E
	Sbrinamento Defrost Defrost	El / Gc	Gc
	Refrigerante Coolant Coolant		R452A
Condensatore Condensator Condensator	Ventole Fans Fans	n°x Ø	2X254
	Portata aria Air flow Air flow	m ³ /h	2100
Evaporatore Evaporator Evaporator	Ventole Fans Fans	n°x Ø	2X200
	Portata aria Air flow Air flow	m ³ /h	1100
	Gittata Air-throw Air-throw	m	m.5
Dimensioni Sizes Sizes	Larghezza Width Width	mm	900
	Profondità Depth Depth	mm	830
	Altezza Height Height	mm	920
	Peso Weight Weight	kg	85

TABELLA DI SELEZIONE | SELECTION TABLE | AUSWAHLTABELLE

m³

W

TA +20°C	TC +5°C	29	2562
	TC 0°C	21,9	2141
	TC -5°C	16,4	1795
TA +32°C	TC +5°C	21,8	2059
	TC 0°C	16,6	1699
	TC -5°C	12,3	1409
TA +43°C	TC +5°C	16,3	1738
	TC 0°C	12	1397
	TC -5°C	9,1	1153