

MONOBLOCKS AND REFRIGERATED SYSTEMS STRADDLE MOUNTING

Straddle mounting as standard, optional panel through the wall installation

- Electronic control instrument
- Expansion device: capillary tube
- Cable for door heater (on all low temperature units)
- Cable for cold room lighting
- Fixed calibration low pressure switch
- High pressure switch on all three-phase units and on single-phase models
- ACM122-152 (this outfit complies with the provisions of the "pressure equipment directive 97/23/CE)
- Condensate evaporation tray with safety overflow drain
- Drain heater
- Hermetic compressor
- Hot gas defrost
- Filter on the liquid line
- Prearrangement for door micro switch connection



TN +5°C/-5°C

DATI TECNICI | TECHNICAL DATA | TECHNICAL DATA

ACM250

Unità Unit Unit	Tensione Voltage Voltage	volt/f/Hz	400/3/50
	Assorbimento Absorption Absorption	W	3100
	Compressore Compressor Kompressor	m ³ /h	9,86
	Tipo comp. Comp. Type Comp. Type	E/S	E
	Sbrinamento Defrost Defrost	El / Gc	Gc
	Refrigerante Coolant Coolant		R452A
Condensatore Condensator Condensator	Ventole Fans Fans	n°x Ø	1X350
	Portata aria Air flow Air flow	m ³ /h	2200
Evaporatore Evaporator Evaporator	Ventole Fans Fans	n°x Ø	1X350
	Portata aria Air flow Air flow	m ³ /h	2400
	Gittata Air-throw Air-throw	m	m.11
Dimensioni Sizes Sizes	Larghezza Width Width	mm	1210
	Profondità Depth Depth	mm	850
	Altezza Height Height	mm	1030
	Peso Weight Weight	kg	135

TABELLA DI SELEZIONE | SELECTION TABLE | AUSWAHLTABELLE

m³

W

TA +20°C	TC +5°C	97,3	5910
	TC 0°C	72,4	4756
	TC -5°C	57	3950
TA +32°C	TC +5°C	78,5	4730
	TC 0°C	54,8	3740
	TC -5°C	38,2	3220
TA +43°C	TC +5°C	49,2	3654
	TC 0°C	34,6	3070
	TC -5°C	27	2610