

MONOBLOCKS AND REFRIGERATED SYSTEMS STRADDLE MOUNTING

Straddle mounting as standard, optional panel through the wall installation

- Electronic control instrument
- Expansion device: capillary tube
- Cable for door heater (on all low temperature units)
- Cable for cold room lighting
- Fixed calibration low pressure switch
- High pressure switch on all three-phase units and on single-phase models
- ACM122-152 (this outfit complies with the provisions of the "pressure equipment directive 97/23/CE)
- Condensate evaporation tray with safety overflow drain
- Drain heater
- Hermetic compressor
- Hot gas defrost
- Filter on the liquid line
- Prearrangement for door micro switch connection



BT -18°C/-25°C

DATI TECNICI | TECHNICAL DATA | TECHNICAL DATA

ACL230

Unità Unit Unit	Tensione Voltage Voltage	volt/f/Hz	400/3/50
	Assorbimento Absorption Absorption	W	2630
	Compressore Compressor Kompressor	m ³ /h	11,54
	Tipo comp. Comp. Type Comp. Type	E/S	E
	Sbrinamento Defrost Defrost	El / Gc	Gc
	Refrigerante Coolant Coolant		R452A
Condensatore Condensator Condensator	Ventole Fans Fans	n°x Ø	2X254
	Portata aria Air flow Air flow	m ³ /h	2100
Evaporatore Evaporator Evaporator	Ventole Fans Fans	n°x Ø	2X200
	Portata aria Air flow Air flow	m ³ /h	1100
	Gittata Air-throw Air-throw	m	m.5
Dimensioni Sizes Sizes	Larghezza Width Width	mm	900
	Profondità Depth Depth	mm	830
	Altezza Height Height	mm	920
	Peso Weight Weight	kg	96

TABELLA DI SELEZIONE | SELECTION TABLE | AUSWAHLTABELLE

m³

W

TA +20°C	TC -18°C	35	2610
	TC -22°C	26,6	2145
	TC -25°C	20,7	1810
TA +32°C	TC -18°C	21,1	1960
	TC -22°C	15,4	1565
	TC -25°C	12,1	1335
TA +43°C	TC -18°C	15,7	1475
	TC -22°C	11,3	1185
	TC -25°C	8,7	1005