

## MONOBLOCKS AND REFRIGERATED SYSTEMS STRADDLE MOUNTING

Straddle mounting as standard, optional panel through the wall installation

- Electronic control instrument
- Expansion device: capillary tube
- Cable for door heater (on all low temperature units)
- Cable for cold room lighting
- Fixed calibration low pressure switch
- High pressure switch on all three-phase units and on single-phase models
- ACM122-152 (this outfit complies with the provisions of the "pressure equipment directive 97/23/CE)
- Condensate evaporation tray with safety overflow drain
- Drain heater
- Hermetic compressor
- Hot gas defrost
- Filter on the liquid line
- Prearrangement for door micro switch connection



## BT -18°C/-25°C

### DATI TECNICI | TECHNICAL DATA | TECHNICAL DATA

ACL300

<b>Unità</b> <b>Unit</b> <b>Unit</b>	Tensione   Voltage   Voltage	volt/f/Hz	400/3/50
	Assorbimento   Absorption   Absorption	W	2400
	Compressore   Compressor   Kompressor	m <sup>3</sup> /h	12,92
	Tipo comp.   Comp. Type   Comp. Type	E/S	E
	Sbrinamento   Defrost   Defrost	El / Gc	Gc
	Refrigerante   Coolant   Coolant		R452A
<b>Condensatore</b> <b>Condensator</b> <b>Condensator</b>	Ventole   Fans   Fans	n°x Ø	1X300
	Portata aria   Air flow   Air flow	m <sup>3</sup> /h	1610
<b>Evaporatore</b> <b>Evaporator</b> <b>Evaporator</b>	Ventole   Fans   Fans	n°x Ø	1X300
	Portata aria   Air flow   Air flow	m <sup>3</sup> /h	1770
	Gittata   Air-throw   Air-throw	m	m,7,5
<b>Dimensioni</b> <b>Sizes</b> <b>Sizes</b>	Larghezza   Width   Width	mm	1160
	Profondità   Depth   Depth	mm	840
	Altezza   Height   Height	mm	1030
	Peso   Weight   Weight	kg	129

### TABELLA DI SELEZIONE | SELECTION TABLE | AUSWAHLTABELLE

m<sup>3</sup>

W

<b>TA +20°C</b>	<b>TC -18°C</b>	38,8	<b>3110</b>
	<b>TC -22°C</b>	30,8	<b>2652</b>
	<b>TC -25°C</b>	24,8	<b>2334</b>
<b>TA +32°C</b>	<b>TC -18°C</b>	27,7	<b>2535</b>
	<b>TC -22°C</b>	21,2	<b>2125</b>
	<b>TC -25°C</b>	17	<b>1887</b>
<b>TA +43°C</b>	<b>TC -18°C</b>	20,7	<b>2037</b>
	<b>TC -22°C</b>	15,5	<b>1687</b>
	<b>TC -25°C</b>	12,7	<b>1455</b>