

MONOBLOCKS AND REFRIGERATED SYSTEMS STRADDLE MOUNTING

Straddle mounting as standard, optional panel through the wall installation

- Electronic control instrument
- Expansion device: capillary tube
- Cable for door heater (on all low temperature units)
- Cable for cold room lighting
- Fixed calibration low pressure switch
- High pressure switch on all three-phase units and on single-phase models
- ACM122-152 (this outfit complies with the provisions of the "pressure equipment directive 97/23/CE)
- Condensate evaporation tray with safety overflow drain
- Drain heater
- Hermetic compressor
- Hot gas defrost
- Filter on the liquid line
- Prearrangement for door micro switch connection



BT -18°C/-25°C

DATI TECNICI | TECHNICAL DATA | TECHNICAL DATA

ACL400

Unità Unit Unit	Tensione Voltage Voltage	volt/f/Hz	400/3/50
	Assorbimento Absorption Absorption	W	3180
	Compressore Compressor Kompressor	m ³ /h	17,59
	Tipo comp. Comp. Type Comp. Type	E/S	E
	Sbrinamento Defrost Defrost	El / Gc	Gc
	Refrigerante Coolant Coolant		R452A
Condensatore Condensator Condensator	Ventole Fans Fans	n°x Ø	1X300
	Portata aria Air flow Air flow	m ³ /h	1610
Evaporatore Evaporator Evaporator	Ventole Fans Fans	n°x Ø	1X300
	Portata aria Air flow Air flow	m ³ /h	1770
	Gittata Air-throw Air-throw	m	m,7,5
Dimensioni Sizes Sizes	Larghezza Width Width	mm	1160
	Profondità Depth Depth	mm	840
	Altezza Height Height	mm	1030
	Peso Weight Weight	kg	131

TABELLA DI SELEZIONE | SELECTION TABLE | AUSWAHLTABELLE

			m ³	W
TA +20°C	TC -18°C		52,8	3532
	TC -22°C		43	3077
	TC -25°C		36,6	2742
TA +32°C	TC -18°C		34,7	2782
	TC -22°C		27,6	2362
	TC -25°C		22,8	2083
TA +43°C	TC -18°C		26,4	2246
	TC -22°C		20,3	1810
	TC -25°C		15,2	1521