

## MONOBLOCKS AND REFRIGERATED SYSTEMS STRADDLE MOUNTING

Straddle mounting as standard, optional panel through the wall installation

Electronic control instrument  
Expansion device: capillary tube  
Cable for door heater (on all low temperature units)  
Cable for cold room lighting  
Fixed calibration low pressure switch  
High pressure switch on all three-phase units and on single-phase models  
ACM122-152 (this outfit complies with the provisions of the "pressure equipment directive 97/23/CE)  
Condensate evaporation tray with safety overflow drain  
Drain heater  
Hermetic compressor  
Hot gas defrost  
Filter on the liquid line  
Prearrangement for door micro switch connection



# TN +5°C/-5°C

### DATI TECNICI | TECHNICAL DATA | TECHNICAL DATA

SCM034

<b>Unità</b> <b>Unit</b> <b>Unit</b>	Tensione   Voltage   Voltage	volt/f/Hz	230/1/50
	Assorbimento   Absorption   Absorption	W	1160
	Compressore   Compressor   Kompressor	m <sup>3</sup> /h	3,03
	Tipo comp.   Comp. Type   Comp. Type	E/S	E
	Sbrinamento   Defrost   Defrost	El / Gc	Gc
	Refrigerante   Coolant   Coolant		R452A
<b>Condensatore</b> <b>Condensator</b> <b>Condensator</b>	Ventole   Fans   Fans	n°x Ø	1X254
	Portata aria   Air flow   Air flow	m <sup>3</sup> /h	1050
<b>Evaporatore</b> <b>Evaporator</b> <b>Evaporator</b>	Ventole   Fans   Fans	n°x Ø	1X200
	Portata aria   Air flow   Air flow	m <sup>3</sup> /h	550
	Gittata   Air-throw   Air-throw	m	m.5
<b>Dimensioni</b> <b>Sizes</b> <b>Sizes</b>	Larghezza   Width   Width	mm	900
	Profondità   Depth   Depth	mm	450
	Altezza   Height   Height	mm	920
	Peso   Weight   Weight	kg	57

### TABELLA DI SELEZIONE | SELECTION TABLE | AUSWAHLTABELLE

		m <sup>3</sup>	W
<b>TA +20°C</b>	<b>TC +5°C</b>	20,8	<b>1843</b>
	<b>TC 0°C</b>	16,6	<b>1570</b>
	<b>TC -5°C</b>	12,4	<b>1328</b>
<b>TA +32°C</b>	<b>TC +5°C</b>	16	<b>1493</b>
	<b>TC 0°C</b>	11,7	<b>1261</b>
	<b>TC -5°C</b>	9,1	<b>1055</b>
<b>TA +43°C</b>	<b>TC +5°C</b>	10,5	<b>1243</b>
	<b>TC 0°C</b>	8,1	<b>1049</b>
	<b>TC -5°C</b>	6	<b>873</b>