

## MONOBLOCKS AND REFRIGERATED SYSTEMS COMMERCIAL CEILING MOUNTED

### COMMERCIAL CEILING-MOUNTED

- Electronic control panel
- Expansion by means of capillary tube
- Cable for door heater (on low temperature units)
- Cable for cold room light
- Fixed calibration low pressure switch
- High pressure switch on all three-phase units and on single-phase CCM122-152 (in compliance with the "pressure equipment" directive 97/23/CE)
- Direct drainage of condensate water with heater
- Hermetic compressor
- Hot gas defrost
- Filter on the liquid line
- Remote control panel connected to the unit with a 5m long cable
- Prearrangement for door micro switch connection



## TN +5°C/-5°C

### DATI TECNICI | TECHNICAL DATA | TECHNICAL DATA

**CMM034**

<b>Unità</b> <b>Unit</b> <b>Unit</b>	Tensione   Voltage   Voltage	volt/f/Hz	230/1/50
	Assorbimento   Absorption   Absorption	W	1160
	Compressore   Compressor   Kompressor	m <sup>3</sup> /h	3,03
	Tipo comp.   Comp. Type   Comp. Type	E/S	E
	Sbrinamento   Defrost   Defrost	EI / Gc	Gc
	Refrigerante   Coolant   Coolant		R452A
<b>Condensatore</b> <b>Condensator</b> <b>Condensator</b>	Ventole   Fans   Fans	n°x Ø	1X254
	Portata aria   Air flow   Air flow	m <sup>3</sup> /h	1050
<b>Evaporatore</b> <b>Evaporator</b> <b>Evaporator</b>	Ventole   Fans   Fans	n°x Ø	1X200
	Portata aria   Air flow   Air flow	m <sup>3</sup> /h	550
	Gittata   Air-throw   Air-throw	m	m.5
<b>Dimensioni</b> <b>Sizes</b> <b>Sizes</b>	Larghezza   Width   Width	mm	650
	Profondità   Depth   Depth	mm	600
	Altezza   Height   Height	mm	930
	Peso   Weight   Weight	kg	64

### TABELLA DI SELEZIONE | SELECTION TABLE | AUSWAHLTABELLE

		m <sup>3</sup>	W
<b>TA +20°C</b>	<b>TC +5°C</b>	20,8	<b>1843</b>
	<b>TC 0°C</b>	16,6	<b>1570</b>
	<b>TC -5°C</b>	12,4	<b>1328</b>
<b>TA +32°C</b>	<b>TC +5°C</b>	16	<b>1493</b>
	<b>TC 0°C</b>	11,7	<b>1261</b>
	<b>TC -5°C</b>	9,1	<b>1055</b>
<b>TA +43°C</b>	<b>TC +5°C</b>	10,5	<b>1243</b>
	<b>TC 0°C</b>	8,1	<b>1049</b>
	<b>TC -5°C</b>	6	<b>873</b>