

MONOBLOCKS AND REFRIGERATED SYSTEMS COMMERCIAL CEILING MOUNTED

COMMERCIAL CEILING-MOUNTED

- Electronic control panel
- Expansion by means of capillary tube
- Cable for door heater (on low temperature units)
- Cable for cold room light
- Fixed calibration low pressure switch
- High pressure switch on all three-phase units and on single-phase CCM122-152 (in compliance with the "pressure equipment" directive 97/23/CE)
- Direct drainage of condensate water with heater
- Hermetic compressor
- Hot gas defrost
- Filter on the liquid line
- Remote control panel connected to the unit with a 5m long cable
- Prearrangement for door micro switch connection



TN +5°C/-5°C

DATI TECNICI | TECHNICAL DATA | TECHNICAL DATA

CMM151

Unità Unit Unit	Tensione Voltage Voltage	volt/f/Hz	400/3/50
	Assorbimento Absorption Absorption	W	2020
	Compressore Compressor Kompressor	m ³ /h	5,69
	Tipo comp. Comp. Type Comp. Type	E/S	E
	Sbrinamento Defrost Defrost	EI / Gc	Gc
	Refrigerante Coolant Coolant		R452A
Condensatore Condensator Condensator	Ventole Fans Fans	n°x Ø	1X300
	Portata aria Air flow Air flow	m ³ /h	1610
Evaporatore Evaporator Evaporator	Ventole Fans Fans	n°x Ø	1X300
	Portata aria Air flow Air flow	m ³ /h	1770
	Gittata Air-throw Air-throw	m	m.7,5
Dimensioni Sizes Sizes	Larghezza Width Width	mm	900
	Profondità Depth Depth	mm	740
	Altezza Height Height	mm	1150
	Peso Weight Weight	kg	108

TABELLA DI SELEZIONE | SELECTION TABLE | AUSWAHLTABELLE

		m ³	W
TA +20°C	TC +5°C	67,7	4472
	TC 0°C	51,4	3746
	TC -5°C	39,3	3154
TA +32°C	TC +5°C	52,7	3556
	TC 0°C	38,4	2940
	TC -5°C	28,8	2442
TA +43°C	TC +5°C	34,8	2825
	TC 0°C	25,9	2366
	TC -5°C	19,5	1949