

## MONOBLOCKS AND REFRIGERATED SYSTEMS COMMERCIAL CEILING MOUNTED

### COMMERCIAL CEILING-MOUNTED

- Electronic control panel
- Expansion by means of capillary tube
- Cable for door heater (on low temperature units)
- Cable for cold room light
- Fixed calibration low pressure switch
- High pressure switch on all three-phase units and on single-phase CCM122-152 (in compliance with the "pressure equipment" directive 97/23/CE)
- Direct drainage of condensate water with heater
- Hermetic compressor
- Hot gas defrost
- Filter on the liquid line
- Remote control panel connected to the unit with a 5m long cable
- Prearrangement for door micro switch connection



# BT -18°C/-25°C

### DATI TECNICI | TECHNICAL DATA | TECHNICAL DATA

CML210

<b>Unità</b> <b>Unit</b> <b>Unit</b>	Tensione   Voltage   Voltage	volt/f/Hz	230/1/50
	Assorbimento   Absorption   Absorption	W	1460
	Compressore   Compressor   Kompressor	m <sup>3</sup> /h	5,99
	Tipo comp.   Comp. Type   Comp. Type	E/S	E
	Sbrinamento   Defrost   Defrost	El / Gc	Gc
	Refrigerante   Coolant   Coolant		R452A
<b>Condensatore</b> <b>Condensator</b> <b>Condensator</b>	Ventole   Fans   Fans	n°x Ø	2X254
	Portata aria   Air flow   Air flow	m <sup>3</sup> /h	2100
<b>Evaporatore</b> <b>Evaporator</b> <b>Evaporator</b>	Ventole   Fans   Fans	n°x Ø	2X200
	Portata aria   Air flow   Air flow	m <sup>3</sup> /h	1100
	Gittata   Air-throw   Air-throw	m	m.5
<b>Dimensioni</b> <b>Sizes</b> <b>Sizes</b>	Larghezza   Width   Width	mm	900
	Profondità   Depth   Depth	mm	650
	Altezza   Height   Height	mm	980
	Peso   Weight   Weight	kg	94

### TABELLA DI SELEZIONE | SELECTION TABLE | AUSWAHLTABELLE

		m <sup>3</sup>	W
<b>TA +20°C</b>	<b>TC -18°C</b>	15,9	<b>1470</b>
	<b>TC -22°C</b>	11,2	<b>1190</b>
	<b>TC -25°C</b>	10,5	<b>1055</b>
<b>TA +32°C</b>	<b>TC -18°C</b>	10,1	<b>1082</b>
	<b>TC -22°C</b>	7,2	<b>865</b>
	<b>TC -25°C</b>	5,5	<b>733</b>
<b>TA +43°C</b>	<b>TC -18°C</b>	7,5	<b>810</b>
	<b>TC -22°C</b>	5	<b>638</b>
	<b>TC -25°C</b>	3,7	<b>528</b>