

MONOBLOCKS AND REFRIGERATED SYSTEMS COMMERCIAL CEILING MOUNTED

COMMERCIAL CEILING-MOUNTED

- Electronic control panel
- Expansion by means of capillary tube
- Cable for door heater (on low temperature units)
- Cable for cold room light
- Fixed calibration low pressure switch
- High pressure switch on all three-phase units and on single-phase CCM122-152 (in compliance with the "pressure equipment" directive 97/23/CE)
- Direct drainage of condensate water with heater
- Hermetic compressor
- Hot gas defrost
- Filter on the liquid line
- Remote control panel connected to the unit with a 5m long cable
- Prearrangement for door micro switch connection



BT -18°C/-25°C

DATI TECNICI | TECHNICAL DATA | TECHNICAL DATA

CML220

Unità Unit Unit	Tensione Voltage Voltage	volt/f/Hz	400/3/50
	Assorbimento Absorption Absorption	W	1810
	Compressore Compressor Kompressor	m ³ /h	9,26
	Tipo comp. Comp. Type Comp. Type	E/S	E
	Sbrinamento Defrost Defrost	El / Gc	Gc
	Refrigerante Coolant Coolant		R452A
Condensatore Condensator Condensator	Ventole Fans Fans	n°x Ø	2X254
	Portata aria Air flow Air flow	m ³ /h	2100
Evaporatore Evaporator Evaporator	Ventole Fans Fans	n°x Ø	2X200
	Portata aria Air flow Air flow	m ³ /h	1100
	Gittata Air-throw Air-throw	m	m.5
Dimensioni Sizes Sizes	Larghezza Width Width	mm	900
	Profondità Depth Depth	mm	650
	Altezza Height Height	mm	980
	Peso Weight Weight	kg	100

TABELLA DI SELEZIONE | SELECTION TABLE | AUSWAHLTABELLE

			m ³	W
TA +20°C	TC -18°C		21,3	2022
	TC -22°C		16,9	1720
	TC -25°C		14	1511
TA +32°C	TC -18°C		14,2	1566
	TC -22°C		10,6	1310
	TC -25°C		8,6	1133
TA +43°C	TC -18°C		10,1	1215
	TC -22°C		7,5	994
	TC -25°C		5,8	844