

MONOBLOCKS AND REFRIGERATED SYSTEMS COMMERCIAL SPLIT UNITS

Commercial Split Units

- Electronic control panel
- Expansion by means of thermal expansion valve
- Cable for door heater (on low temperature units)
- Fixed calibration low pressure switch
- High pressure switch on all three-phase units and on single-phase HMM122-152 (in compliance with the "pressure equipment" directive 97/23/CE)
- Direct drainage of condensate water with heater
- Hermetic compressor
- Electric defrost
- Filter on the liquid line
- Remote control panel connected to the unit with a 5m long cable
- Sight glass
- All units are equipped with a liquid receiver complying (in compliance with the "pressure equipment" directive 97/23/CE)
- Pre-arrangement for door switch and room light connections



TN +5°C/-5°C

DATI TECNICI | TECHNICAL DATA | TECHNICAL DATA

HMM012

Unità Unit Unit	Tensione Voltage Voltage	volt/f/Hz	230/1/50
	Assorbimento Absorption Absorption	W	730
	Compressore Compressor Kompressor	m ³ /h	2,11
	Tipo comp. Comp. Type Comp. Type	E/S	E
	Sbrinamento Defrost Defrost	EI / Gc	550
	Refrigerante Coolant Coolant		R452A
Condensatore Condensator Condensator	Ventole Fans Fans	n°x Ø	1X254
	Portata aria Air flow Air flow	m ³ /h	1050
Evaporatore Evaporator Evaporator	Ventole Fans Fans	n°x Ø	1X254
	Portata aria Air flow Air flow	m ³ /h	810
	Gittata Air-throw Air-throw	m	m.6
Dimensioni Sizes Sizes	Larghezza Width Width	mm	850 (C) / 710 (E)
	Profondità Depth Depth	mm	690 (C) / 620 (E)
	Altezza Height Height	mm	640 (C) / 390 (E)
	Peso Weight Weight	kg	62 (C) / 20 (E)

TABELLA DI SELEZIONE | SELECTION TABLE | AUSWAHLTABELLE

			m ³	W
TA +20°C	TC +5°C		16,2	1445
	TC 0°C		12,6	1194
	TC -5°C		8,3	1045
TA +32°C	TC +5°C		12	1076
	TC 0°C		9	970
	TC -5°C		6,5	815
TA +43°C	TC +5°C		7,9	932
	TC 0°C		5,7	745
	TC -5°C		3,7	595